

**Product configuration: EJ33+GOBO40B**

EJ33: Spotlight with Profiler – Warm White LED – Ta 25

GOBO40B: Gobo ø40mm - min focusing



EJ33: Spotlight with Profiler – Warm White LED – Ta 25

### Technical description

Spotlight for outdoor use with profile designed to use LED lamps. Consists of an optical assembly and a base. The optical assembly, arm and base and frame holder are made of aluminium alloy and subjected to a multi-step, pre-treatment process, in which the main phases are degreasing, fluorozirconation (a protective surface film) and sealing (with a nano-structured silane layer). The painting stage consists of a primer and a liquid acrylic paint, cured at 150 °C, with a high level of weather resistance. 5 mm thick extra-clear tempered sodium-calcium closing glass. Secured using a 360° adjustable base. Adjustable horizontally. Includes a graduated scale with a position lock. Complete with LED circuit and Opti Beam optic system. The product is supplied with Ø40mm and Ø30mm gobos that allow 25° and 20° light cones and blades to define specific magnetically mountable forms. The chance to use dichroic glass gobos (via assembly with a gobo holder and an image rotation system) or in sheet metal (via a magnetic assembly). The product includes a PG9 cable gland. Electronic DALI ballast integrated in product. Option of installing a SPD to increase voltage spike protection. All external screws used are made of A2 stainless steel.

## Installation

**Installation**  
Floor, wall, ceiling or ground-installed via a stake.



White (01) | Black (04) | Grey (15) | Rust Brown (F5)


## Weight (Kg)

7.35

## Wiring

Double PG.

Complies with EN60598-1 and pertinent regulations



Im system:	2093	Life Time LED 1:	50,000h - L80 - B10 (Ta 25°C)
W system:	63.3	Lamp code:	LED
Im source:	8050	Number of lamps for optical assembly:	1
W source:	57	ZVEI Code:	LED
Luminous efficiency (Im/W, real value):	33.1	Number of optical assemblies:	1
Im in emergency mode:	-	Intervallo temperatura ambiente:	from -30°C to 35°C.
Total light flux at or above an angle of 90° [Lm]:	0	Lifetime of product at ambient operating temperature:	≥ 50.000h Ta=25°C
Light Output Ratio (L.O.R.) [%]:	26	Power factor:	See installation instructions
CRI (minimum):	80	Overvoltage protection:	10kV Common mode & 6kV Differential mode
Colour temperature [K]:	3000	Control:	DALI-2
MacAdam Step:	3		

## Polar

