



Last information update: October 2024

Product configuration: EN22+GOBO2

EN22: Ø 30mm spotlight with Profiler – Neutral White LED
GOBO2: Gobo ø2 mm



Product code

EN22: Ø 30mm spotlight with Profiler – Neutral White LED

Technical description

Spotlight for outdoor use with profiler designed to use LED lamps. Consists of an optical assembly and a base. The optical assembly, arm and base and frame holder are made of aluminium alloy and subjected to a multi-step, pre-treatment process, in which the main phases are degreasing, fluorozirconation (a protective surface film) and sealing (with a nano-structured silane layer). The painting stage consists of a primer and a liquid acrylic paint, cured at 150 °C, with a high level of weather resistance. 5mm thick extra-clear tempered sodium-calcium closing glass. Secured using a 360° adjustable base. Adjustable horizontally. Includes a graduated scale with a position lock. Complete with LED circuit and Opti Beam optic system. Supplied with 4 gobos with Ø 2,3,4,5mm diameter central opening. Black rubber outlet cable complete with anti-transpiration device. Electronic ballast to be ordered separately. All external screws used are made of A2 stainless steel.

Installation

Floor, wall, ceiling or ground-installed via a stake.

Colour

White (01) | Black (04) | Grey (15) | Rust Brown (F5)

Weight (Kg)

0.28

Wiring

The product is supplied with a black rubber outlet cable complete with anti-transpiration device.

Notes

The surge protectors depend on the power feeders chosen.

Complies with EN60598-1 and pertinent regulations



Technical data

Im system:	6	MacAdam Step:	2
W system:	2.5	Life Time LED 1:	56,000h - L80 - B10 (Ta 25°C)
Im source:	300	Life Time LED 2:	56,000h - L80 - B10 (Ta 40°C)
W source:	2.5	Lamp code:	LED
Luminous efficiency (Im/W, real value):	2.4	Number of lamps for optical assembly:	1
Im in emergency mode:	-	ZVEI Code:	LED
Total light flux at or above an angle of 90° [Lm]:	0	Number of optical assemblies:	1
Light Output Ratio (L.O.R.) [%]:	2	Intervalllo temperatura ambiente:	from -30°C to 50°C.
CRI (minimum):	80	Lifetime of product at ambient operating temperature:	≥ 50.000h Ta=40°C
Colour temperature [K]:	4000	LED current [mA]:	850

Polar

