


Product configuration: EN26+GOBO30A

EN26: Ø 116mm spotlight with Profiler – Warm White LED – Ta 40

GOBO30A: Gobo ø30mm - max focusing



EN26: Ø 116mm spotlight with Profiler – Warm White LED – Ta 40

Spotlight for outdoor use with prolier designed to use LED lamps. Consists of an optical assembly and a base. The optical assembly, arm and base and frame holder are made of aluminium alloy and subjected to a multi-step, pre-treatment process, in which the main phases are degreasing, fluorozirconation (a protective surface film) and sealing (with a nano-structured silane layer). The painting stage consists of a primer and a liquid acrylic paint, cured at 150 °C, with a high level of weather resistance. 5 mm thick extra-clear tempered sodium-calcium closing glass. Secured using a 360° adjustable base. Adjustable horizontally. Includes a graduated scale with a position lock. Complete with LED circuit and Opti Beam optic system. The product is supplied with Ø40mm and Ø30mm gobos that allow 26° and 18° light cones and blades to define specific magnetically mountable forms. The chance to use dichroic glass gobos (via assembly with a gobo holder and an image rotation system) or in sheet metal (via a magnetic assembly). The product includes a PG9 cable gland. Electronic DALI ballast integrated in product. Option of installing a SPD to increase voltage spike protection. All external screws used are made of A2 stainless steel.

Installation
Floor, wall, ceiling or ground-installed via a stake.

White (01) | Black (04) | Grey (15) | Rust Brown (F5)

5.45

Double PG.

Voltage spike protection: 2kV Common Mode and 1kV Differential Mode.

Complies with EN60598-1 and pertinent regulations



lm system:	816	Life Time LED 2:	100,000h - L90 - B10 (Ta 40°C)
W system:	27.8	Lamp code:	LED
lm source:	3400	Number of lamps for optical assembly:	1
W source:	24	ZVEI Code:	LED
Luminous efficiency (lm/W, real value):	29.4	Number of optical assemblies:	1
lm in emergency mode:	-	Intervallo temperatura ambiente:	from -20°C to +35°C. (*)
Total light flux at or above an angle of 90° [Lm]:	0	Power factor:	See installation instructions
Light Output Ratio (L.O.R.) [%]:	24	Inrush current:	20 A / 50 µs
CRI (minimum):	80	Maximum number of luminaires of this type per miniature circuit breaker:	B10A: 34 luminaires B16A: 55 luminaires C10A: 57 luminaires C16A: 93 luminaires
Colour temperature [K]:	2700	Minimum dimming %:	1
MacAdam Step:	2	Overvoltage protection:	2kV Common mode & 2kV Differential mode
Life Time LED 1:	100,000h - L90 - B10 (Ta 25°C)	Control:	DALI-2

* Preliminary data

Polar

