


Design iGuzzini iGuzzini

Product configuration: MK52.43

Product configuration: MK52.43
MK52.43: 10 - cell Recessed luminaire - LED Neutral white Flood optic - 23.5W 1683.5lm - 4000K - CRI 95 - Black / Black



MK52.43: 10 - cell Recessed luminaire - LED Neutral white Flood optic - 23.5W 1683.5lm - 4000K - CRI 95 - Black / Black

rectangular miniaturised recessed luminaire with 10 optical elements with LED lamps - fixed optics - flood beam angle. Main body with die-cast aluminium radiant surface, version with perimeter surface frame. Metallised thermoplastic high definition optics, integrated in a rear position in the black anti-glare screen; the structure of the optical system prevents a pinpoint effect, allowing precise, circular light distribution and emission with controlled glare . Supplied with DALI dimmable electronic control gear connected to the luminaire. Neutral white high colour rendering LED.

recessed with steel wire springs for false ceilings from 1 to 25 mm thick - preparation hole 37 x 274

Colour
Black / Black (43)

Weight (Kg)
0.65

mounting
wall recessed|ceiling recessed

on control gear box with quick-coupling connections

Complies with EN60598-1 and pertinent regulations



Im system:	1683	CRI (typical):	97
W system:	23.5	Colour temperature [K]:	4000
Im source:	2030	MacAdam Step:	3
W source:	20	Life Time LED 1:	50,000h - L90 - B10 (Ta 25°C)
Luminous efficiency (Im/W, real value):	71.6	Lamp code:	LED
Im in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	83	Number of optical assemblies:	1
Beam angle [°]:	48°	Control:	DALI-2
CRI (minimum):	95		

	CIE nL 0.83 100-100-100-100-83 UGR <10-10	Lux <table border="1"> <thead> <tr> <th>h</th> <th>d</th> <th>Em</th> <th>E_{max}</th> </tr> </thead> <tbody> <tr> <td>2</td> <td>1.8</td> <td>624</td> <td>744</td> </tr> <tr> <td>4</td> <td>3.6</td> <td>156</td> <td>186</td> </tr> <tr> <td>6</td> <td>5.4</td> <td>69</td> <td>83</td> </tr> <tr> <td>8</td> <td>7.1</td> <td>39</td> <td>46</td> </tr> </tbody> </table>	h	d	Em	E _{max}	2	1.8	624	744	4	3.6	156	186	6	5.4	69	83	8	7.1	39	46
	h		d	Em	E _{max}																	
	2		1.8	624	744																	
	4		3.6	156	186																	
	6		5.4	69	83																	
8	7.1	39	46																			
DIN A.61																						
UTE 0.83A+0.00T F*1=999 F*1+F*2=1000 F*1+F*2+F*3=1000																						
CIBSE LG3 L<1500 cd/m ² at 65° UGR<10 L<1500 cd/mq @65°																						

Utilisation factors

R	77	75	73	71	55	53	33	00	DRR
K0.8	75	71	68	66	70	68	68	65	78
1.0	78	75	72	70	74	72	71	69	83
1.5	82	79	77	76	79	77	76	74	89
2.0	85	83	81	80	82	80	79	77	93
2.5	86	85	84	83	84	83	82	79	96
3.0	87	86	85	85	85	84	83	81	98
4.0	88	87	87	86	86	86	84	82	99
5.0	89	88	88	88	87	86	85	83	100

UGR diagram

Corrected UGR values (at 2030 lm bare lamp luminous flux)											
Reflect.:		viewed crosswise					viewed endwise				
ceiling/cav		0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30
walls		0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30
work pl.		0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
Room dim											
x	y										
2H	2H	2.0	2.5	2.3	2.7	3.0	2.0	2.5	2.3	2.7	3.0
	3H	1.9	2.3	2.2	2.6	2.9	1.9	2.3	2.2	2.6	2.9
	4H	1.8	2.2	2.2	2.5	2.8	1.8	2.2	2.2	2.5	2.8
	6H	1.8	2.1	2.1	2.4	2.8	1.8	2.1	2.1	2.4	2.8
	8H	1.7	2.1	2.1	2.4	2.7	1.7	2.1	2.1	2.4	2.7
	12H	1.7	2.0	2.1	2.4	2.7	1.7	2.0	2.1	2.4	2.7
4H	2H	1.8	2.2	2.2	2.5	2.8	1.8	2.2	2.2	2.5	2.8
	3H	1.7	2.0	2.1	2.4	2.7	1.7	2.0	2.1	2.4	2.7
	4H	1.6	1.9	2.0	2.3	2.7	1.6	1.9	2.0	2.3	2.7
	6H	1.5	1.8	1.9	2.2	2.6	1.5	1.8	1.9	2.2	2.6
	8H	1.5	1.7	1.9	2.1	2.6	1.5	1.7	1.9	2.1	2.6
	12H	1.4	1.6	1.9	2.1	2.5	1.4	1.6	1.9	2.1	2.5
8H	4H	1.5	1.7	1.9	2.1	2.6	1.5	1.7	1.9	2.1	2.6
	6H	1.4	1.6	1.8	2.0	2.5	1.4	1.6	1.8	2.0	2.5
	8H	1.3	1.5	1.8	2.0	2.5	1.3	1.5	1.8	2.0	2.5
	12H	1.3	1.4	1.8	1.9	2.4	1.3	1.4	1.8	1.9	2.4
12H	4H	1.4	1.6	1.9	2.1	2.5	1.4	1.6	1.9	2.1	2.5
	6H	1.3	1.5	1.8	2.0	2.5	1.3	1.5	1.8	2.0	2.5
	8H	1.3	1.4	1.8	1.9	2.4	1.3	1.4	1.8	1.9	2.4
Variations with the observer position at spacing:											
S =		1.0H	0.9 / -18.0				0.9 / -18.0				
		1.5H	9.7 / -18.3				9.7 / -18.3				
		2.0H	11.7 / -18.4				11.7 / -18.4				