


Last information update: April 2025

**Product configuration: N098**

N098: adjustable luminaire - Ø 153 mm - warm white - flood optic - frame

**Product code**

N098: adjustable luminaire - Ø 153 mm - warm white - flood optic - frame

**Technical description**

Round adjustable luminaire designed to use an LED lamp with C.O.B. technology in a warm white colour tone 3000K. Version with rim for surface-mounting. Painted, die-cast aluminium body. Lower reflector vacuum-metallised with aluminium vapours with an anti-scratch protective layer. Anodised aluminium upper reflector. Black, zinc-plated sheet steel bracket. The luminaire can be rotated 30° relative to the horizontal plane and 358° about the vertical axis. The luminaire is fitted with mechanical locks for light beam aiming. Painted extruded aluminium dissipater.

**Installation**

Recessed using torsion springs which allow easy installation in false ceilings with thickness ranging from 1 mm to 25 mm.

**Colour**

White / Aluminium (39)

**Weight (Kg)**

1.43

**Mounting**

ceiling recessed

**Wiring**

Product complete with DALI components

**Notes**

Tpa rated

Complies with EN60598-1 and pertinent regulations

**Technical data**

lm system:	1600.0	CRI:	80
W system:	24.9	Colour temperature [K]:	3000
lm source:	3200	MacAdam Step:	2
W source:	22	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25C)
Luminous efficiency (lm/W, real value):	64.26	Lamp code:	LED
lm in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0.0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	50	Number of optical assemblies:	1
Beam angle [°]:	26°	Control:	DALI-2