

Last information update: March 2025

**Product configuration: PH35.G1**

PH35.G1: Module for Superrail 48V track - DALI - GL - L=1824 - Continuous line - 25.2W 3536lm - 3500K - CRI 90 - Black/Black Transparent

**Product code**

PH35.G1: Module for Superrail 48V track - DALI - GL - L=1824 - Continuous line - 25.2W 3536lm - 3500K - CRI 90 - Black/Black Transparent

**Technical description**

Linear lighting product with 3500K CRI90 monochrome LED complete with adapter for installation on a Superrail 48V track. General Light (High Output) luminaire with Opti-Diamond Space optic available in a White Cover (Transparent white) or Black Cover (Transparent black) version. The adapter made of a thermoplastic material includes the DC/DC driver circuit with a DALI dimmable function. Integrated «power line» technology allows each light module on the track to be adjusted separately. Frameless version main body made of extruded aluminium. A rapid tool-free system for connecting the adapter electrically and mechanically to the track. Module for continuous line not including caps (to be ordered as an accessory).

**Installation**

Mechanical fastening with adapter on a Superrail 48V track. Close the continuous line with a pair of caps to be ordered separately.

**Colour**

Black/Black Transparent (G1)

**Weight (Kg)**

1.03

**Mounting**

Low voltage track

**Wiring**

Integrated DC/DC LED driver in adapter - direct connection on 48V track. Track power supply unit to be ordered separately.

Complies with EN60598-1 and pertinent regulations

**Technical data**

Im system:	3203	Voltage [Vin]:	48
W system:	25.2	Lamp code:	LED
Im source:	4160	Number of lamps for optical assembly:	1
W source:	24	ZVEI Code:	LED
Luminous efficiency (Im/W, real value):	127.1	Number of optical assemblies:	1
Im in emergency mode:	-	LED current [mA]:	72
Total light flux at or above an angle of 90° [Lm]:	61	Power factor:	See installation instructions
Light Output Ratio (L.O.R.) [%]:	77	Minimum dimming %:	5
CRI (minimum):	90	Overvoltage protection:	2kV Common mode & 1kV Differential mode
Colour temperature [K]:	3500	Dimming mode:	CCR
MacAdam Step:	3	Control:	DALI
Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)		

**Polar**

Imax=3375 cd		C75-255		Lux			
90°	180°	90°	h	d1	d2	Em	Emax
			4	4.6	4.6	162	206
			8	9.2	9.2	40	51
			12	13.8	13.9	18	23
			16	18.4	18.5	10	13
$\alpha = 60^\circ$							

**Isolux**

