

Last information update: December 2024

Product configuration: Q409+Q367.01

Q409: Plate - General Down Light - Neutral LED - DALI - L 1196

Q367.01: Minimal continuous line module - General Down Light - L3594 - White

**Product code**

Q409: Plate - General Down Light - Neutral LED - DALI - L 1196

Technical description

LED module set up for housing in initial or intermediate system profiles - down emission. DALI dimmable electronic control gear integrated in the luminaire. Extruded aluminium heat sink; high emission yield flux enhancer. Neutral LED.

Installation

Module insertion on profiles facilitated by a quick coupling system.

Colour

Indeterminate (00)

Weight (Kg)

1.37

Wiring

Quick coupling terminal block connection to simplify connections between the luminaires. LED module complete with integrated control gear.

Complies with EN60598-1 and pertinent regulations

**Product code**

Q367.01: Minimal continuous line module - General Down Light - L3594 - White

Technical description

Minimal (frameless) version extruded aluminium intermediate profile for flush with ceiling mounting; this allows continuous lines to be created with other intermediate profiles and an initial profile (required). Methacrylate opal screen (diffused general light); screen set up for connecting several lengths by overlapping.

Installation

Installation can be recessed, surface, ceiling and pendant-mounted using suitable accessories to be ordered separately; mechanical systems for connecting modules included in the package.

Colour

White (01)

Weight (Kg)

8.5

Mounting

ceiling recessed|wall surface|ceiling surface|ceiling pendant

Wiring

Set up to house the LED modules required by the system.

Notes

Take care with the system configuration. To complete a continuous line correctly there must always be an initial module at the start or end of the composition.


TPb rated. TPa version available on request, contact iGuzzini for more info

Complies with EN60598-1 and pertinent regulations

**Technical data**

lm system:	11924	Colour temperature [K]:	4000
W system:	120.4	MacAdam Step:	3
lm source:	17800	Life Time LED 1:	> 50,000h - L80 - B10 (Ta 25°C)
W source:	106	Lamp code:	LED
Luminous efficiency (lm/W, real value):	99	Number of lamps for optical assembly:	1
lm in emergency mode:	-	ZVEI Code:	LED
Total light flux at or above an angle of 90° [Lm]:	0	Number of optical assemblies:	1
Light Output Ratio (L.O.R.) [%]:	67	Control:	DALI-2
CRI (minimum):	80		

Polar



Isolux

