



Last information update: November 2024

#### Product configuration: QA85+QB54.01

QA85: Initial moduleFrame DownGeneral LightL 1208

QB54.01: Down HO plate - DALI - General Light - LED Warm - L 1196 - 24.5W 2845lm - 3000K - White



#### Product code

QA85: Initial moduleFrame DownGeneral LightL 1208

#### Technical description

Initial profile in extruded aluminium - Frame version with contact frame; methacrylate opal screen for diffused general light; screen set up for connecting several lengths by overlapping.

#### Installation

Recessed using the brackets on the profile. The initial modules can be used individually (stand-alone), if completed with accessory caps and the required LED module.

#### Colour

White (01)

#### Weight (Kg)

2.55

#### Mounting

ceiling recessed|ceiling pendant

#### Wiring

Set up to house the LED modules required by the system.

#### Notes

Take care with the system configuration. To make continuous lines of lighting, use the intermediate modules. To complete a continuous line correctly there must always be an initial module at the start or end of the composition.

TPb rated. TPa version available on request, contact iGuzzini for more info

Complies with EN60598-1 and pertinent regulations



#### Product code

QB54.01: Down HO plate - DALI - General Light - LED Warm - L 1196 - 24.5W 2845lm - 3000K - White

#### Technical description

LED module set up for housing in initial or intermediate system profiles. Down emission - High Output version for General Light profiles (with opal diffuser screen). The module optic and structural fittings allow high luminous flux and system efficiency values. DALI dimmable control gear integrated in the luminaire. Extruded aluminium heat sink; high emission yield flux enhancer. Warm 3000K LED

#### Installation

Module insertion on profiles facilitated by a quick coupling system.

#### Colour

Indeterminate (00)

#### Weight (Kg)

1.28

#### Wiring

Quick coupling terminal block connection to simplify connections between the subsequent modules. Complete with integrated dimmable digital DALI control gear.

Complies with EN60598-1 and pertinent regulations



#### Technical data

Im system:	2964	CRI (minimum):	80
W system:	24.2	Colour temperature [K]:	3000
Im source:	3900	MacAdam Step:	3
W source:	22	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
Luminous efficiency (Im/W, real value):	122.5	Lamp code:	LED
Im in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	76	Number of optical assemblies:	1

Polar

