



QB18.01: Down LO plate - ON-OFF - General Light - LED Warm - L 1196 - 17W 1825lm - 3000K - White

QA91: Initial moduleMinimal DownGeneral LightL 1208

Initial profile in extruded aluminium - Minimal (frameless) version for flush with ceiling mounting and up-down emission; methacrylate opal screen for diffused general light; screen set up for connecting several lengths by overlapping.

Installation: Installation can be recessed, surface, ceiling and pendant-mounted using suitable accessories to be ordered separately. The initial modules can be used individually for various applications if completed with accessory caps and the required LED module.

Colour	Weight (Kg)
White (01) Black (04) Aluminium (12)	2.35

ceiling recessed|ceiling surface|ceiling pendant

Set up to house the LED modules required by the system.

Take care with the system configuration. To make continuous lines of lighting, use the intermediate modules. To complete a continuous line correctly there must always be an initial module at the start or end of the composition.

TPb rated. TPa version available on request, contact [iguzzini](mailto:iguzzini@iguzzini.com) for more info

Complies with EN60598-1 and pertinent regulations



QB18.01: Down LO plate - ON-OFF - General Light - LED Warm - L 1196 - 17W 1825lm - 3000K - White **Attention! Code no longer in production**

LED module set up for housing in initial or intermediate system profiles. Down emission - Low Output version for General Light profiles (with opal diffuser screen). Electronic control gear integrated in the luminaire. Extruded aluminium heat sink; high emission yield flux enhancer. Warm 3000K LED

Module insertion on profiles facilitated by a quick coupling system.

Colour	Weight (Kg)
Indeterminate (00)	1.28

Quick coupling terminal block connection to simplify connections between the subsequent modules. Complete with integrated ON-OFF - non-dimmable control gear.

Complies with EN60598-1 and pertinent regulations



Im system:	1938	CRI (minimum):	80
W system:	17.1	Colour temperature [K]:	3000
Im source:	2550	MacAdam Step:	3
W source:	15	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
Luminous efficiency (lm/W, real value):	113.3	Lamp code:	LED
Im in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	76	Number of optical assemblies:	1

Polar

