

Last information update: November 2024

Product configuration: QA94+QB13.01

QA94: Module for continuous lineMinimal DownGeneral LightL 898

QB13.01: Down LO plate - DALI - General Light - LED Neutral - L 896 - 12.5W 1458lm - 4000K - White

Product code

QA94: Module for continuous lineMinimal DownGeneral LightL 898

Technical description

Extruded aluminium intermediate profile - Minimal (frameless) version for flush with ceiling mounting; this allows continuous lines to be created with other intermediate profiles and an initial profile (required). Methacrylate opal screen for diffused general light; screen set up for connecting several lengths by overlapping.

Installation

Installation can be recessed, surface, ceiling and pendant-mounted using suitable accessories to be ordered separately; the mechanical systems for connecting the subsequent profiles are included in the package.

Colour

White (01) | Black (04) | Aluminium (12)

Weight (Kg)

1.66

Mounting

ceiling recessed|ceiling surface|ceiling pendant

Wiring

Set up to house the LED modules required by the system.

Notes

Take care with the system configuration. To make continuous lines of lighting, use the intermediate modules. To complete a continuous line correctly there must always be an initial module at the start or end of the composition. TPb rated. TPa version available on request, contact iGuzzini for more info

Complies with EN60598-1 and pertinent regulations

**Product code**

QB13.01: Down LO plate - DALI - General Light - LED Neutral - L 896 - 12.5W 1458lm - 4000K - White

Technical description

LED module set up for housing in initial or intermediate system profiles. Down emission - Low Output version for General Light profiles (with opal diffuser screen). DALI dimmable control gear integrated in the luminaire. Extruded aluminium heat sink; high emission yield flux enhancer. Neutral 4000K LED

Installation

Module insertion on profiles facilitated by a quick coupling system.

Colour

Indeterminate (00)

Weight (Kg)

0.99

Wiring

Quick coupling terminal block connection to simplify connections between the subsequent modules. Complete with integrated dimmable digital DALI control gear.

Complies with EN60598-1 and pertinent regulations

**Technical data**

Im system:	1558	CRI (minimum):	80
W system:	12.9	Colour temperature [K]:	4000
Im source:	2050	MacAdam Step:	3
W source:	11	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
Luminous efficiency (Im/W, real value):	120.8	Lamp code:	LED
Im in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	76	Number of optical assemblies:	1

Polar

