

QA97: Initial module Minimal Up / Down General Light L 2397  
QB28.01: Up / Down LO plate - ON-OFF - General Light - LED Warm - L 1196 - 22W 3800lm - 3000K - White  
N2:  
INCA: Recessed

QA97: Initial module Minimal Up / Down General LightL 2397

Initial profile in extruded aluminium - Minimal (frameless) version for flush with ceiling mounting available for direct and indirect lighting (luminous flux split into approx. 70% down / 30% up.); methacrylate opal lower screen for diffused general light; screen set up for connecting several lengths by overlapping. Methacrylate diffusing screen for upper emission.

Installation can be pendant-mounted using suitable accessories to be ordered separately. The initial modules can be used individually for various applications if completed with accessory caps and the required LED module.

White (01) | Black (04) | Aluminium (12)

## 4.7

ceiling pendant

Set up to house the LED modules required by the system.

Take care with the system configuration. To make continuous lines of lighting, use the intermediate modules. To complete a continuous line correctly there must always be an initial module at the start or end of the composition.

Complies with EN60598-1 and pertinent regulations



QB28.01: Up / Down LO plate - ON-OFF - General Light - LED Warm - L 1196 - 22W 3800lm - 3000K - White **Attention! Code no longer in production**

LED module set up for housing in initial or intermediate system profiles. Up + down emission - Low Output version for General Light profiles (with lower opal diffuser screen). Electronic control gear integrated in the luminaire. Extruded aluminium heat sink; high emission yield flux enhancer. Warm 3000K.

Module insertion on profiles facilitated by a quick coupling system.

Indeterminate (00)


## 1.6

Quick coupling terminal block connection to simplify connections between the subsequent modules. Complete with integrated ON-OFF - non-dimmable control gear.

Complies with EN60598-1 and pertinent regulations



Im system:	5320	CRI:	80
W system:	49.9	Colour temperature [K]:	3000
Im source:	7600	MacAdam Step:	3
W source:	45	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
Luminous efficiency (lm/W, real value):	106.6	Lamp code:	LED
Im in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	1504	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	70	Number of optical assemblies:	1

<p>Imax=1495 cd</p> <p>C85-265</p> 	<p><b>CIE</b>  nL 0.70  50-80-96-72-70  UGR 21.4-21.3</p> <p><b>DIN</b>  B.43</p> <p><b>UTE</b>  0.50E+0.20T  F"1=497  F"1+F"2=802  F"1+F"2+F"3=958</p>
--	---