

Last information update: November 2024

Product configuration: QA98+QB61.01+N3+INCA

QA98: Initial moduleMinimal Up / DownGeneral LightL 3596

QB61.01: Up / Down HO plate - ON-OFF - General Light - LED Warm - L 3588 - 100W 17500lm - 3000K - White

N3:

INCA: Recessed

Product code

QA98: Initial moduleMinimal Up / DownGeneral LightL 3596

Technical description

Initial profile in extruded aluminium - Minimal (frameless) version for flush with ceiling mounting available for direct and indirect lighting (luminous flux split into approx. 70% down / 30% up.); methacrylate opal lower screen for diffused general light; screen set up for connecting several lengths by overlapping. Methacrylate diffusing screen for upper emission.

Installation

Installation can be pendant-mounted using suitable accessories to be ordered separately. The initial modules can be used individually for various applications if completed with accessory caps and the required LED module - L 3588.

Colour

White (01) | Black (04) | Aluminium (12)

Weight (Kg)

7

Mounting

ceiling pendant

Wiring


Set up exclusively to house L 3588 triple-length LED modules.

Notes

Take care with the system configuration. To make continuous lines of lighting, use the intermediate modules. To complete a continuous line correctly there must always be an initial module at the start or end of the composition.

Complies with EN60598-1 and pertinent regulations

IP20



Product code

QB61.01: Up / Down HO plate - ON-OFF - General Light - LED Warm - L 3588 - 100W 17500lm - 3000K - White **Attention! Code no longer in production**

Technical description

LED module set up for housing in intermediate system profiles, ideal for particularly long light lines. Up + down emission - High Output version for General Light profiles (with lower opal diffuser screen). The module optic and structural fittings allow high luminous flux and system efficiency values. Electronic control gear integrated in the luminaire. Extruded aluminium heat sink; high emission yield flux enhancer. Warm 3000K LED

Installation

Module insertion on profiles facilitated by a quick coupling system.

Colour

Indeterminate (00)

Weight (Kg)

3.8

Wiring

Quick coupling terminal block connection to simplify connections between the subsequent modules. Complete with integrated ON-OFF - non-dimmable control gear.

Notes

Important: the triple length intermediate luminous module can be used for both initial profiles - L 3594 - for stand-alone applications, and intermediate profiles - L 3594 - for continuous line applications.

Complies with EN60598-1 and pertinent regulations



Technical data

lm system:	12250	CRI:	80
W system:	114.3	Colour temperature [K]:	3000
lm source:	17500	MacAdam Step:	3
W source:	100	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
Luminous efficiency (lm/W, real value):	107.2	Lamp code:	LED
lm in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	3463	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	70	Number of optical assemblies:	1

Polar

