

Last information update: November 2024

**Product configuration: QA98+QB27.01+N3+INCA**

QA98: Initial module Minimal Up / Down General Light L 3596

QB27.01: Up / Down LO plate - DALI - General Light - LED Neutral - L 3588 - 68W 12200lm - 4000K - White

N3:

INCA: Recessed

**Product code**

QA98: Initial module Minimal Up / Down General Light L 3596

**Technical description**

Initial profile in extruded aluminium - Minimal (frameless) version for flush with ceiling mounting available for direct and indirect lighting (luminous flux split into approx. 70% down / 30% up.); methacrylate opal lower screen for diffused general light; screen set up for connecting several lengths by overlapping. Methacrylate diffusing screen for upper emission.

**Installation**

Installation can be pendant-mounted using suitable accessories to be ordered separately. The initial modules can be used individually for various applications if completed with accessory caps and the required LED module - L 3588.

**Colour**

White (01) | Black (04) | Aluminium (12)

**Weight (Kg)**

7

**Mounting**

ceiling pendant

**Wiring**


Set up exclusively to house L 3588 triple-length LED modules.

**Notes**

Take care with the system configuration. To make continuous lines of lighting, use the intermediate modules. To complete a continuous line correctly there must always be an initial module at the start or end of the composition.

Complies with EN60598-1 and pertinent regulations

IP20

**Product code**

QB27.01: Up / Down LO plate - DALI - General Light - LED Neutral - L 3588 - 68W 12200lm - 4000K - White

**Technical description**

LED module set up for housing in intermediate system profiles, ideal for particularly long light lines. Up + down emission - Low Output version for General Light profiles (with lower opal diffuser screen). DALI dimmable control gear integrated in the luminaire. Extruded aluminium heat sink; high emission yield flux enhancer. Neutral 4000K LED

**Installation**

Module insertion on profiles facilitated by a quick coupling system.

**Colour**

Indeterminate (00)

**Weight (Kg)**

4.8

**Wiring**

Quick coupling terminal block connection to simplify connections between the subsequent modules. Complete with integrated dimmable DALI control gear.

**Notes**

Important: the triple length intermediate luminous module can be used for both initial profiles - L 3594 - for stand-alone applications, and intermediate profiles - L 3594 - for continuous line applications.

Complies with EN60598-1 and pertinent regulations

**Technical data**

lm system:	8540	CRI:	80
W system:	75.3	Colour temperature [K]:	4000
lm source:	12200	MacAdam Step:	3
W source:	68	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
Luminous efficiency (lm/W, real value):	113.4	Lamp code:	LED
lm in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	2414	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	70	Number of optical assemblies:	1

Polar

