

Last information update: November 2024

**Product configuration: QA99+QB63.01+N3+INCA**

QA99: Module for continuous lineMinimal Up / DownGeneral LightL 3596  
QB63.01: Up / Down HO plate - DALI - General Light - LED Warm - L 3588 - 100W 17500lm - 3000K - White  
N3:  
INCA: Recessed

**Product code**

QA99: Module for continuous lineMinimal Up / DownGeneral LightL 3596

**Technical description**

Extruded aluminium intermediate profile - Minimal (frameless) version for flush with ceiling mounting available for direct and indirect lighting (luminous flux split into approx. 70% down / 30% up.). This allows continuous lines to be created with other intermediate profiles and an initial profile (required). Methacrylate opal lower screen for diffused general light; screen set up for connecting several lengths by overlapping. Methacrylate diffusing screen for upper emission.

**Installation**

Installation can be pendant-mounted using suitable accessories to be ordered separately; the mechanical systems for connecting the subsequent profiles are included in the package.

**Colour**

White (01) | Black (04) | Aluminium (12)

**Weight (Kg)**

7

**Mounting**

ceiling pendant

**Wiring**


Set up exclusively to house L 3588 triple-length LED modules.

**Notes**

Take care with the system configuration. To make continuous lines of lighting, use the intermediate modules. To complete a continuous line correctly there must always be an initial module at the start or end of the composition.

Complies with EN60598-1 and pertinent regulations

IP20



**Product code**

QB63.01: Up / Down HO plate - DALI - General Light - LED Warm - L 3588 - 100W 17500lm - 3000K - White

**Technical description**

LED module set up for housing in intermediate system profiles, ideal for particularly long light lines. Up + down emission - High Output version for General Light profiles (with lower opal diffuser screen). The module optic and structural fittings allow high luminous flux and system efficiency values. DALI dimmable control gear integrated in the luminaire. Extruded aluminium heat sink; high emission yield flux enhancer. Warm 3000K LED

**Installation**

Module insertion on profiles facilitated by a quick coupling system.

**Colour**

Indeterminate (00)

**Weight (Kg)**

3.8

**Wiring**

Quick coupling terminal block connection to simplify connections between the subsequent modules. Complete with integrated dimmable digital DALI control gear.

**Notes**

Important: the triple length intermediate luminous module can be used for both initial profiles - L 3594 - for stand-alone applications, and intermediate profiles - L 3594 - for continuous line applications.

Complies with EN60598-1 and pertinent regulations



**Technical data**

lm system:	12250	CRI:	80
W system:	110.6	Colour temperature [K]:	3000
lm source:	17500	MacAdam Step:	3
W source:	100	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
Luminous efficiency (lm/W, real value):	110.8	Lamp code:	LED
lm in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	3463	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	70	Number of optical assemblies:	1

Polar

