

## Product Environmental Profile of luminaires for indoor lighting - Light Shed (with polycarbonate housing) family

Reference product: R900.715



Registration number	IGUZ-00006-V01.01-EN	Drafting rules	PCR-ed4-EN-2021 09 06
		Supplemented by	PSR-0014-ed1.0-EN2018 07 18
Verifier accreditation number	VH04	Information and reference documents	<a href="http://www.pep-ecopassport.org">www.pep-ecopassport.org</a>
Date of issue	04-2023	Validity period	5 years

Independent verification of the declaration and data, in compliance with ISO 14025: 2006

Internal		External	x
----------	--	----------	---

The PCR review was conducted by a panel of experts chaired by Julie ORGELET (DDemain)

PEP are compliant with XP C08-100-1:2016 or EN 50693:2019

The elements of the present PEP cannot be compared with elements from another program.

Document in compliance with ISO 14025 : 2006 « Environmental labels and declarations. Type III environmental declarations»



## General information

### Company information:

iGuzzini illuminazione S.p.A via Mariano Guzzini, 37 62019, Recanati, Italy

Web Site available at: <https://www.iguzzini.com/it/>

Legal contact: Cristiano Venturini (info.hq@iguzzini.com)

### Reference product:

“Light Shed R900.715”

The assessed product range covers indoor lighting luminaires from the “Light Shed” family with polycarbonate housing, hereinafter called Light Shed\_STD\_PC. The luminaires are used for professional lighting of indoor environments, mainly used for workplaces as well as a decorative finish for Hospitality & Retail applications.

The main technical features of the reference product R900.715 are described in the table below.

Characteristics	Unit	Light Shed_STD_PC family
Product code	-	R900.715
Light source	-	Integrated LED module
LED module code	-	1.192.121.00
Power supply	-	OSRAM 35W
Color temperature	K	4000
Protection index for water and dust (IP)	-	IP20/IP43
Impact resistance index (IK)	-	IK02
Nominal operating voltage	V	220-240
Assigned lifetime	Hours	50.000
Declaration lifetime of the LED module	Hours	50.000
Useful output flux	Lumen	3724
Electrical power	W	29,2
Luminous efficiency	Lumen/W	127,5
Dimension	mm	556 x 556 x 104

#### Functional unit:

“Provide lighting that delivers an outgoing artificial luminous flux of 1,000 lumens during a reference lifetime of 35,000 hours”.

The reference flow is calculated as:

(1,000/outgoing luminous flux of the analyzed product in lumens) x (35,000/declared product lifetime of the analyzed product in hours):

$$(1.000/3.724) \times (35.000/50.000) = 0,188$$

#### Homogeneous environmental family:

The reference product represents the Light Shed\_STD\_PC luminaires family, which differs in terms of power and useful output flux (lumen).


The range of variations for the products in the same family is the following:

Light Shed_STD_PC family	Unit	Value for the reference product	Minimum value in product range	Maximum value in product range
Electrical power	W	29,2	23,1	29,3
Useful output flux	Lumen	3724	2394	3724

The present PEP declaration is valid for all the products in the described homogenous environmental family. The spreadsheet provided as annex shall be used by the PEP user to extrapolate the impact of the other products from the Light Shed\_STD\_PC family, based on the technical parameters of the considered product, as requested by the PSR.




## Constituent materials




### METALS

	kg	%
Steel	0,1240	3,35
Brass	0,0008	0,02



### PLASTICS

	kg	%
Polycarbonate (PC)	0,7760	20,35
Polypropylene (PP)	0,4300	11,27
Polymethyl methacrylate (PMMA)	0,2361	6,19
Polyethylene terephthalate (PET)	0,0219	0,57
Silicon	0,0012	0,03
Polyester	0,0007	0,02



### OTHER MATERIALS

	kg	%
Electronical components	0,3442	9,02
Paper	0,0251	0,66
Cardboard - Packaging	1,0094	26,47
Plastic (PE) - Packaging	0,0947	2,48
Wood - Packaging	0,7500	19,66

<b>Total reference product</b>	<b>1,960</b>	<b>51,4%</b>
<b>Total packaging</b>	<b>1,854</b>	<b>48,6%</b>
<b>TOTAL</b>	<b>3,814</b>	<b>100%</b>

The list above includes also materials with a certain amount of recycled content, in order to reduce the impacts linked to the production of virgin materials. In particular:

- The paperboard box of packaging is made of 100% of recycled content;
- The plastic bag used for packaging is made of 100% of recycled content;
- The pallet used for shipment is reused.



## Manufacture

The product components are manufactured or assembled by iGuzzini S.p.A. in Recanati (Italy) manufacturing site. iGuzzini applies an environmental management system, certified according to ISO 14001:2015 and an energy management system certified according to ISO 50001:2018 (the certificates are available at: <https://www.iguzzini.com/it/certificazioni/>).

In 2023 iGuzzini gained the gold medal in the EcoVadis platform.

In 2022, iGuzzini disclosed its sustainability performances within the Fagerhult Group Sustainability Report. In the same year iGuzzini plant of Recanati passed to 100% green energy procurement verified and certified by GO (origin guarantee certificates).

All lighting products manufactured by iGuzzini comply to the European directive “2011/65/EU ROHS 2 - Restriction of dangerous substances in electrical and electronical equipment”.



## Distribution

There is no hub for the distribution. Products leaving the production site in Recanati (MC), Italy, are delivered directly to the final clients. The distribution of the final destinations is the following:

Destination	Share (%)	Type transport considered
Italy	33%	Local
France	48%	Intercontinental
Germany	6%	Intercontinental
Spain	5%	Intercontinental
Switzerland	3%	Intercontinental
Poland	1%	Intercontinental
England	1%	Intercontinental
Argentina	1%	Intracontinental
New Zealand	1%	Intracontinental
Finland	1%	Intercontinental



## Installation

The luminaires are provided to the client with the power supply, the fixing elements and the assembly elements, fittings and other electrical connectors needed for installation. Therefore, the installation of the luminaire does not require additional components and the product is easily installed using manual tools. In this phase the end of life (EoL) of the packaging of the final product is considered as well.



## Use

Energy efficient light sources (LED lighting) are integrated. The use phase consists of electricity use during the whole lifetime of the product. The assigned lifetime of the luminaire is the same as for the integrated LED module (50,000 hours), as specified in the PSR-0014-ed1.0-EN-2018 07 18 (Average lifetime of light sources = 50,000 hours).



## End of life

The company is affiliated with a WEEE (Waste Electrical and Electronic Equipment) Italian consortium (Ecolight, <https://ecolight.it/>). The product at its end of life is managed as prescribed by the current legislation about EEE waste (Directive 2012/19/EU) and the waste treatment scenarios of the Countries in which the product is distributed. According to the most recent data available, waste treatment scenarios are the following:

Scenario	Recycling	Incineration (with energy recovery)	Incineration (without energy recovery)	Landfill	Modeling assumptions
Italy	95%	2%	0%	3%	Transport (150 km) and treatment of waste based on Ecolight statistics
France	77%	8,50%	6%	8,50%	Transport (1000 km) and treatment of waste based on PSR statistics
Germany	54%	-	-	46%	Transport (1000 km) and treatment of waste based on recycling statistics of Global E-waste Monitor
Spain	34%	-	-	66%	Transport (1000 km) and treatment of waste based on recycling statistics of Global E-waste Monitor
Switzerland	34%	-	-	66%	Transport (1000 km) and treatment of waste based on recycling statistics of Global E-waste Monitor
Poland	23%	-	-	77%	Transport (1000 km) and treatment of waste based on recycling statistics of Global E-waste Monitor
England	59%	-	-	41%	Transport (1000 km) and treatment of waste based on recycling statistics of Global E-waste Monitor
Argentina	1%	-	-	99%	Transport (1000 km) and treatment of waste based on recycling statistics of Global E-waste Monitor
New Zealand	9%	-	-	91%	Transport (1000 km) and treatment of waste based on recycling statistics of Global E-waste Monitor
Finland	59%	-	-	41%	Transport (1000 km) and treatment of waste based on recycling statistics of Global E-waste Monitor



## Environmental impacts

The evaluation of environmental impacts examines the manufacturing, distribution, installation, use and end-of-life stages of the Reference Product life cycle.

The environmental impacts assessment of the reference product has been performed using SimaPro 9.4.0.2 software. Background datasets have been retrieved from Ecoinvent 3.8 libraries. The impact indicators and impact models used are the ones indicated by the PCR-ed4-EN-2021 09 06. This environmental declaration has been developed considering an outgoing artificial luminous flux of 1,000 lumens over a reference lifetime of 35,000 hours (Functional Unit).

**Results of mandatory indicators per F.U. (for 1.000 lumens during 35.000 hours) of R900.715 luminaire:**

Impact category	Unit	Total	Manufacturing	Distribution	Installation	Use	EoL
Climate change	kg CO <sub>2</sub> eq	7,37E+01	3,21E+00	8,05E-01	8,69E-02	6,95E+01	6,72E-02
Ozone depletion	kg CFC-11 eq	7,17E-06	2,35E-07	1,83E-07	4,60E-09	6,74E-06	6,06E-09
Photochemical ozone formation	kg NMVOC eq	1,69E-01	1,04E-02	4,41E-03	1,04E-04	1,54E-01	1,53E-04
Acidification	mol H <sup>+</sup> eq	3,59E-01	2,12E-02	4,19E-03	8,48E-05	3,33E-01	1,33E-04
Eutrophication, freshwater	kg P eq	3,26E-02	8,19E-04	1,76E-05	1,22E-06	3,17E-02	1,93E-06
Eutrophication, marine	kg N eq	6,28E-02	3,17E-03	1,52E-03	8,75E-05	5,78E-02	1,69E-04
Eutrophication, terrestrial	mol N eq	6,04E-01	3,13E-02	1,67E-02	2,76E-04	5,56E-01	5,01E-04
Water requirement	m <sup>3</sup> depriv.	3,51E+01	1,18E+00	1,28E-02	1,09E-03	3,39E+01	1,69E-03
Abiotic resource depletion, fossils	MJ	2,50E+03	4,56E+01	1,14E+01	3,03E-01	2,45E+03	3,94E-01
Abiotic resource depletion, minerals and metals	kg Sb eq	1,22E-03	2,43E-04	6,33E-07	4,53E-08	9,79E-04	6,08E-08
Climate change - Fossil	kg CO <sub>2</sub> eq	6,92E+01	3,16E+00	8,05E-01	1,98E-02	6,52E+01	4,98E-02
Climate change - Biogenic	kg CO <sub>2</sub> eq	4,27E+00	3,45E-02	3,22E-04	6,29E-02	4,16E+00	1,64E-02
Climate change - Land use and LU change	kg CO <sub>2</sub> eq	1,08E-01	9,41E-03	9,05E-05	6,93E-06	9,87E-02	9,29E-06

**Results of mandatory indicators per unit of product (declared unit, 3.724 lumens during 50.000 hours) of R900.715 luminaire:**

Impact category	Unit	Total	Manufacturing	Distribution	Installation	Use	EoL
Climate change	kg CO <sub>2</sub> eq	3,92E+02	1,71E+01	4,28E+00	4,62E-01	3,70E+02	3,57E-01
Ozone depletion	kg CFC-11 eq	3,81E-05	1,25E-06	9,74E-07	2,45E-08	3,58E-05	3,23E-08
Photochemical ozone formation	kg NMVOC eq	9,00E-01	5,53E-02	2,35E-02	5,53E-04	8,19E-01	8,14E-04
Acidification	mol H <sup>+</sup> eq	1,91E+00	1,13E-01	2,23E-02	4,51E-04	1,77E+00	7,06E-04
Eutrophication, freshwater	kg P eq	1,73E-01	4,36E-03	9,38E-05	6,50E-06	1,69E-01	1,03E-05
Eutrophication, marine	kg N eq	3,34E-01	1,68E-02	8,11E-03	4,65E-04	3,08E-01	9,01E-04
Eutrophication, terrestrial	mol N eq	3,22E+00	1,66E-01	8,88E-02	1,47E-03	2,96E+00	2,67E-03
Water requirement	m <sup>3</sup> depriv.	1,87E+02	6,29E+00	6,80E-02	5,78E-03	1,81E+02	8,99E-03
Abiotic resource depletion, fossils	MJ	1,33E+04	2,43E+02	6,06E+01	1,61E+00	1,30E+04	2,10E+00
Abiotic resource depletion, minerals and metals	kg Sb eq	6,51E-03	1,29E-03	3,37E-06	2,41E-07	5,21E-03	3,24E-07
Climate change - Fossil	kg CO <sub>2</sub> eq	3,68E+02	1,68E+01	4,28E+00	1,05E-01	3,47E+02	2,65E-01
Climate change - Biogenic	kg CO <sub>2</sub> eq	2,27E+01	1,84E-01	1,71E-03	3,35E-01	2,21E+01	8,72E-02
Climate change - Land use and LU change	kg CO <sub>2</sub> eq	5,76E-01	5,00E-02	4,82E-04	3,69E-05	5,25E-01	4,94E-05

**Results of mandatory indicators per unit of product (R900.715 luminaire) - Detail of the use phase with the decomposition of module B (B1-B7) according to EN 15978 and EN 15804:**

Impact category	Unit	Total	B1	B2	B3	B4	B5	B6	B7
Climate change	kg CO <sub>2</sub> eq	3,70E+02	-	-	-	-	-	3,70E+02	-
Ozone depletion	kg CFC-11 eq	3,58E-05	-	-	-	-	-	3,58E-05	-
Photochemical ozone formation	kg NMVOC eq	8,19E-01	-	-	-	-	-	8,19E-01	-
Acidification	mol H <sup>+</sup> eq	1,77E+00	-	-	-	-	-	1,77E+00	-
Eutrophication, freshwater	kg P eq	1,69E-01	-	-	-	-	-	1,69E-01	-
Eutrophication, marine	kg N eq	3,08E-01	-	-	-	-	-	3,08E-01	-
Eutrophication, terrestrial	mol N eq	2,96E+00	-	-	-	-	-	2,96E+00	-
Water requirement	m <sup>3</sup> depriv.	1,81E+02	-	-	-	-	-	1,81E+02	-
Abiotic resource depletion, fossils	MJ	1,30E+04	-	-	-	-	-	1,30E+04	-
Abiotic resource depletion, minerals and metals	kg Sb eq	5,21E-03	-	-	-	-	-	5,21E-03	-
Climate change - Fossil	kg CO <sub>2</sub> eq	3,47E+02	-	-	-	-	-	3,47E+02	-
Climate change - Biogenic	kg CO <sub>2</sub> eq	2,21E+01	-	-	-	-	-	2,21E+01	-
Climate change - Land use and LU change	kg CO <sub>2</sub> eq	5,25E-01	-	-	-	-	-	5,25E-01	-

Within the determination of the impacts of the manufacturing, installation, use and end of life the choice of the dataset relating to electricity consumption fell on low voltage energy (230 V) for all the geographical areas considered in the study. Furthermore, energy mixes were used for each country.

**Results of mandatory inventory flow indicators per F.U. (for 1.000 lumens during 35.000 hours) of R900.715 luminaire:**

Indicators	Unit	Value
Renewable primary energy (without raw material)	MJ	4,15E+02
Renewable primary energy (raw material)	MJ	2,08E+00
Total use of renewable primary energy	MJ	4,17E+02
Non renewable primary energy (without raw material)	MJ	2,52E+03
Non renewable primary energy (raw material)	MJ	4,16E+01
Total use of non-renewable primary energy	MJ	2,56E+03
Use of secondary materials	kg	2,17E-01
Use of renewable secondary fuels	MJ	-
Use of non-renewable secondary fuels	MJ	2,35E+00
Net use of fresh water	m <sup>3</sup>	3,76E-05
Hazardous waste disposed	kg	2,19E-03
Non-hazardous waste disposed	kg	5,32E-02
Radioactive waste disposed	kg	-
Components for reuse	kg	1,41E-01
Materials for recycling	kg	*
Materials for energy recovery	kg	*
Exported energy	MJ	-
Biogenic carbon content of the product	kg	4,72E-03
Biogenic carbon content of the associated packaging	kg	3,31E-01

*The use of the symbol \* indicates that the value depends on the country where the WEEE is disposed*



Results of mandatory inventory flow indicators per unit of product (declared unit, 3.724 lumens during 50.000 hours) of R900.715 luminaire:

Indicators	Unit	Value
Renewable primary energy (without raw material)	MJ	2,21E+03
Renewable primary energy (raw material)	MJ	1,11E+01
Total use of renewable primary energy	MJ	2,22E+03
Non renewable primary energy (without raw material)	MJ	1,34E+04
Non renewable primary energy (raw material)	MJ	2,21E+02
Total use of non-renewable primary energy	MJ	1,36E+04
Use of secondary materials	kg	1,16E+00
Use of renewable secondary fuels	MJ	-
Use of non-renewable secondary fuels	MJ	1,25E+01
Net use of fresh water	m <sup>3</sup>	2,00E-04
Hazardous waste disposed	kg	1,16E-02
Non-hazardous waste disposed	kg	2,83E-01
Radioactive waste disposed	kg	-
Components for reuse	kg	7,50E-01
Materials for recycling	kg	*
Materials for energy recovery	kg	*
Exported energy	MJ	-
Biogenic carbon content of the product	kg	2,51E-02
Biogenic carbon content of the associated packaging	kg	1,76E+00

*The use of the symbol \* indicates that the value depends on the country where the WEEE is disposed*



## Extrapolation rules

Extrapolations rules have been calculated following PCR-ed4-EN-2021 09 06 and PSR-0014-ed1.0-EN-2018 07 18. The defined rules shall be applied using the Extrapolation rules file provided in the following tables.

Parameter	Value for reference product (R900.715)
Lighting output [lumens]	3724
Weight of light source [kg]	0,0012
Weight of luminaire structure and his packaging [kg]	3,667
Weight of power equipment [kg]	0,145
Weight of light management system [kg]	-
Weight of product including its light source (no packaging) [kg]	1,960
Weight of product including its packaging [kg]	3,814
Power [W]	29,2

The extrapolation coefficients calculation at the functional unit level shall be taken into account with the following formula:

$$\text{Extrapolation coefficient at the product level} \times \frac{\text{Lighting output of reference product (lumen)}}{\text{Lighting output of concerned product (lumens)}}$$

## Extrapolation coefficients

The reported extrapolation coefficients are intended at product level (declared unit) and not at functional unit.

Product Code	Manufacturing	Distribution	Installation	Use	EoL
R868.715	1,000	1,000	1,000	0,791	1,000
R868.716	1,000	1,000	1,000	0,791	1,000
R868.781	1,000	1,000	1,000	0,791	1,000
R868.7E8	1,000	1,000	1,000	0,791	1,000
R869.715	1,000	1,000	1,000	0,791	1,000
R869.716	1,000	1,000	1,000	0,791	1,000
R869.781	1,000	1,000	1,000	0,791	1,000
R869.7E8	1,000	1,000	1,000	0,791	1,000
R870.715	1,000	1,000	1,000	0,791	1,000
R870.716	1,000	1,000	1,000	0,791	1,000
R870.781	1,000	1,000	1,000	0,791	1,000
R870.7E8	1,000	1,000	1,000	0,791	1,000
R871.715	1,000	1,000	1,000	0,791	1,000
R871.716	1,000	1,000	1,000	0,791	1,000
R871.781	1,000	1,000	1,000	0,791	1,000
R871.7E8	1,000	1,000	1,000	0,791	1,000
R872.715	1,000	1,000	1,000	0,805	1,000
R872.716	1,000	1,000	1,000	0,805	1,000
R872.781	1,000	1,000	1,000	0,805	1,000
R872.7E8	1,000	1,000	1,000	0,805	1,000
R873.715	1,000	1,000	1,000	0,805	1,000
R873.716	1,000	1,000	1,000	0,805	1,000
R873.781	1,000	1,000	1,000	0,805	1,000
R873.7E8	1,000	1,000	1,000	0,805	1,000
R874.715	1,000	1,000	1,000	0,805	1,000
R874.716	1,000	1,000	1,000	0,805	1,000
R874.781	1,000	1,000	1,000	0,805	1,000
R874.7E8	1,000	1,000	1,000	0,805	1,000
R875.715	1,000	1,000	1,000	0,805	1,000
R875.716	1,000	1,000	1,000	0,805	1,000
R875.781	1,000	1,000	1,000	0,805	1,000
R875.7E8	1,000	1,000	1,000	0,805	1,000
R896.715	1,000	1,000	1,000	1,003	1,000
R896.716	1,000	1,000	1,000	1,003	1,000
R896.781	1,000	1,000	1,000	1,003	1,000
R896.7E8	1,000	1,000	1,000	1,003	1,000
R897.715	1,000	1,000	1,000	1,003	1,000
R897.716	1,000	1,000	1,000	1,003	1,000
R897.781	1,000	1,000	1,000	1,003	1,000
R897.7E8	1,000	1,000	1,000	1,003	1,000
R898.715	1,000	1,000	1,000	1,003	1,000
R898.716	1,000	1,000	1,000	1,003	1,000

R898.781	1,000	1,000	1,000	1,003	1,000
R898.7E8	1,000	1,000	1,000	1,003	1,000
R899.715	1,000	1,000	1,000	1,003	1,000
R899.716	1,000	1,000	1,000	1,003	1,000
R899.781	1,000	1,000	1,000	1,003	1,000
R899.7E8	1,000	1,000	1,000	1,003	1,000
R900.715	1,000	1,000	1,000	1,000	1,000
R900.716	1,000	1,000	1,000	1,000	1,000
R900.781	1,000	1,000	1,000	1,000	1,000
R900.7E8	1,000	1,000	1,000	1,000	1,000
R901.715	1,000	1,000	1,000	1,000	1,000
R901.716	1,000	1,000	1,000	1,000	1,000
R901.781	1,000	1,000	1,000	1,000	1,000
R901.7E8	1,000	1,000	1,000	1,000	1,000
R902.715	1,000	1,000	1,000	1,000	1,000
R902.716	1,000	1,000	1,000	1,000	1,000
R902.781	1,000	1,000	1,000	1,000	1,000
R902.7E8	1,000	1,000	1,000	1,000	1,000
R903.715	1,000	1,000	1,000	1,000	1,000
R903.716	1,000	1,000	1,000	1,000	1,000
R903.781	1,000	1,000	1,000	1,000	1,000
R903.7E8	1,000	1,000	1,000	1,000	1,000

The following table reports the informations of the products included in the homogeneous environmental family.

Product Code	System power (Watt)	Total weight (Kg)	Housing weight (Kg)	Structure weight + Packaging weight (Kg)	Power supply weight (Kg)	Lighting Source weight (Kg)	Packaging weight (Kg)	Luminaries weight (Kg)
R868.715	23,1	3,814	0,75	3,6679	0,145	0,0012	1,854	1,960
R868.716	23,1	3,814	0,75	3,6679	0,145	0,0012	1,854	1,960
R868.781	23,1	3,814	0,75	3,6679	0,145	0,0012	1,854	1,960
R868.7E8	23,1	3,814	0,75	3,6679	0,145	0,0012	1,854	1,960
R869.715	23,1	3,814	0,75	3,6679	0,145	0,0012	1,854	1,960
R869.716	23,1	3,814	0,75	3,6679	0,145	0,0012	1,854	1,960
R869.781	23,1	3,814	0,75	3,6679	0,145	0,0012	1,854	1,960
R869.7E8	23,1	3,814	0,75	3,6679	0,145	0,0012	1,854	1,960
R870.715	23,1	3,814	0,75	3,6679	0,145	0,0012	1,854	1,960
R870.716	23,1	3,814	0,75	3,6679	0,145	0,0012	1,854	1,960
R870.781	23,1	3,814	0,75	3,6679	0,145	0,0012	1,854	1,960
R870.7E8	23,1	3,814	0,75	3,6679	0,145	0,0012	1,854	1,960
R871.715	23,1	3,814	0,75	3,6679	0,145	0,0012	1,854	1,960
R871.716	23,1	3,814	0,75	3,6679	0,145	0,0012	1,854	1,960
R871.781	23,1	3,814	0,75	3,6679	0,145	0,0012	1,854	1,960
R871.7E8	23,1	3,814	0,75	3,6679	0,145	0,0012	1,854	1,960
R872.715	23,5	3,814	0,75	3,6679	0,145	0,0012	1,854	1,960
R872.716	23,5	3,814	0,75	3,6679	0,145	0,0012	1,854	1,960
R872.781	23,5	3,814	0,75	3,6679	0,145	0,0012	1,854	1,960
R872.7E8	23,5	3,814	0,75	3,6679	0,145	0,0012	1,854	1,960
R873.715	23,5	3,814	0,75	3,6679	0,145	0,0012	1,854	1,960
R873.716	23,5	3,814	0,75	3,6679	0,145	0,0012	1,854	1,960
R873.781	23,5	3,814	0,75	3,6679	0,145	0,0012	1,854	1,960
R873.7E8	23,5	3,814	0,75	3,6679	0,145	0,0012	1,854	1,960
R874.715	23,5	3,814	0,75	3,6679	0,145	0,0012	1,854	1,960
R874.716	23,5	3,814	0,75	3,6679	0,145	0,0012	1,854	1,960
R874.781	23,5	3,814	0,75	3,6679	0,145	0,0012	1,854	1,960
R874.7E8	23,5	3,814	0,75	3,6679	0,145	0,0012	1,854	1,960
R875.715	23,5	3,814	0,75	3,6679	0,145	0,0012	1,854	1,960
R875.716	23,5	3,814	0,75	3,6679	0,145	0,0012	1,854	1,960
R875.781	23,5	3,814	0,75	3,6679	0,145	0,0012	1,854	1,960
R875.7E8	23,5	3,814	0,75	3,6679	0,145	0,0012	1,854	1,960
R896.715	29,3	3,814	0,75	3,6679	0,145	0,0012	1,854	1,960
R896.716	29,3	3,814	0,75	3,6679	0,145	0,0012	1,854	1,960
R896.781	29,3	3,814	0,75	3,6679	0,145	0,0012	1,854	1,960
R896.7E8	29,3	3,814	0,75	3,6679	0,145	0,0012	1,854	1,960
R897.715	29,3	3,814	0,75	3,6679	0,145	0,0012	1,854	1,960
R897.716	29,3	3,814	0,75	3,6679	0,145	0,0012	1,854	1,960
R897.781	29,3	3,814	0,75	3,6679	0,145	0,0012	1,854	1,960
R897.7E8	29,3	3,814	0,75	3,6679	0,145	0,0012	1,854	1,960
R898.715	29,3	3,814	0,75	3,6679	0,145	0,0012	1,854	1,960
R898.716	29,3	3,814	0,75	3,6679	0,145	0,0012	1,854	1,960

R898.781	29,3	3,814	0,75	3,6679	0,145	0,0012	1,854	1,960
R898.7E8	29,3	3,814	0,75	3,6679	0,145	0,0012	1,854	1,960
R899.715	29,3	3,814	0,75	3,6679	0,145	0,0012	1,854	1,960
R899.716	29,3	3,814	0,75	3,6679	0,145	0,0012	1,854	1,960
R899.781	29,3	3,814	0,75	3,6679	0,145	0,0012	1,854	1,960
R899.7E8	29,3	3,814	0,75	3,6679	0,145	0,0012	1,854	1,960
R900.715	29,2	3,814	0,75	3,6679	0,145	0,0012	1,854	1,960
R900.716	29,2	3,814	0,75	3,6679	0,145	0,0012	1,854	1,960
R900.781	29,2	3,814	0,75	3,6679	0,145	0,0012	1,854	1,960
R900.7E8	29,2	3,814	0,75	3,6679	0,145	0,0012	1,854	1,960
R901.715	29,2	3,814	0,75	3,6679	0,145	0,0012	1,854	1,960
R901.716	29,2	3,814	0,75	3,6679	0,145	0,0012	1,854	1,960
R901.781	29,2	3,814	0,75	3,6679	0,145	0,0012	1,854	1,960
R901.7E8	29,2	3,814	0,75	3,6679	0,145	0,0012	1,854	1,960
R902.715	29,2	3,814	0,75	3,6679	0,145	0,0012	1,854	1,960
R902.716	29,2	3,814	0,75	3,6679	0,145	0,0012	1,854	1,960
R902.781	29,2	3,814	0,75	3,6679	0,145	0,0012	1,854	1,960
R902.7E8	29,2	3,814	0,75	3,6679	0,145	0,0012	1,854	1,960
R903.715	29,2	3,814	0,75	3,6679	0,145	0,0012	1,854	1,960
R903.716	29,2	3,814	0,75	3,6679	0,145	0,0012	1,854	1,960
R903.781	29,2	3,814	0,75	3,6679	0,145	0,0012	1,854	1,960
R903.7E8	29,2	3,814	0,75	3,6679	0,145	0,0012	1,854	1,960