

Last information update: April 2025

**Product configuration: RU00+RU45+RV14**

RV14: Plate with Neutral White LED - Downlight - General Light LO - DALI - L=1196

**Product code**

RV14: Plate with Neutral White LED - Downlight - General Light LO - DALI - L=1196

**Technical description**

Neutral White LED plate with direct (Down) light emission. Low Output (LO) version for General Light profiles to connect to the relevant Opal screen (single or roll) to be ordered separately. The module optic and structural fittings allow high system efficiency values to be achieved. DALI dimmable power supply integrated in the luminaire. Extruded aluminium heat sink and "Halogen Free" electric cables.

**Installation**

Module insertion on profiles facilitated by a quick coupling system.

**Colour**

White (01)

**Weight (Kg)**

0.83

**Wiring**

Quick coupling terminal block connection to simplify connections between the subsequent modules. Complete with integrated dimmable DALI power supply.

Complies with EN60598-1 and pertinent regulations

**Technical data**

Im system:	1735.5	CRI:	90
W system:	16.3	Colour temperature [K]:	4000
Im source:	2670	MacAdam Step:	3
W source:	14	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25C)
Luminous efficiency (Im/W, real value):	106.47	Lamp code:	LED
Im in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0.0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	65	Number of optical assemblies:	1
Beam angle [°]:	97° / 102°	Control:	DALI-2