

Product configuration: UC92

Product code

Technical description

Installation

Colour
Black (04) | Grey (15)

Weight (Kg)
7.1

Mounting

span-wire installation


Complies with EN60598-1 and pertinent regulations




Technical data

Im system:	2479	Life Time LED 2:	100,000h - L90 - B10 (Ta 40°C)
W system:	16	Lamp code:	LED
Im source:	-	Number of lamps for optical assembly:	1
W source:	-	ZVEI Code:	LED
Luminous efficiency (lm/W, real value):	154.9	Number of optical assemblies:	1
Im in emergency mode:	-	Intervallo temperatura ambiente:	from -15°C to 40°C.
Total light flux at or above an angle of 90° [Lm]:	0	Power factor:	See installation instructions
Light Output Ratio (L.O.R.) [%]:	100	Inrush current:	20.3 A / 346 µs
CRI (minimum):	70	Maximum number of luminaires of this type per miniature circuit breaker:	B10A: 10 luminaires B16A: 17 luminaires C10A: 17 luminaires C16A: 28 luminaires
Colour temperature [K]:	4000	Minimum dimming %:	1
MacAdam Step:	3	Overvoltage protection:	12kV Common mode & 12kV Differential mode
Life Time LED 1:	100,000h - L90 - B10 (Ta 25°C)		

Polar



Isolux



Utilisation factors

