Design iGuzzini


iGuzzini

Last information update: March 2025

Product configuration: EX07

EX07: Pole-mounted system - ST1 optic - Warm White - ø 46-60-76mm - Zhaga Up







## **Product code**

EX07: Pole-mounted system - ST1 optic - Warm White - ø 46-60-76mm - Zhaga Up

## Technical description

Outdoor luminaire with direct light street optic, designed to use LED lamps. The optical assembly and the pole attachment system are made of EN1706AC 46100LF aluminium alloy and subjected to a multi-step, pre-treatment process, in which the main phases are: degreasing, fluorozirconation (a protective surface film) and sealing (with a nano-structured silane layer). The painting stage consists of a primer and a textured liquid acrylic paint, cured at 150 °C, with a high level of weather and UV ray resistance. Option of adjusting the inclination in relation to the road surface by +20°-5° (in 5° steps) for a pole-top installation and +5°/20° (in 5° steps) for a lateral installation. 5 mm thick extra-clear sodium-calcium closure glass fastened to the product with 4 screws. The high IP rating is guaranteed by the silicone gasket placed between the two elements. Complete with circuit featuring monochrome LEDs and polymer optic lenses. Product fitted with a multi-pole Zhaga 4 Pin socket. Driver with automatic internal temperature control system. The wiring and optical compartment can be opened with everyday tools or tool-free devices. The luminous flux emitted in the upper hemisphere of the system in the horizontal position is null (in conformity with the strictest standards for the prevention of light pollution). All external screws are made of stainless steel.

## Installation

The spotlight can be installed with a pole-top or lateral mounting.

 Colour
 Weight (Kg)

 White (01) | Black (04) | Grey (15) | Rust Brown (F5)
 6.05

# Mounting

wall arm|poletop bottom entry

# Notes

In the event of installations on insulated supports (like fibreglass poles) it is mandatory (or strongly recommended) to use the accessory code X899 to protect the luminaire from eventual faults due to electrostatic charges.

Complies with EN60598-1 and pertinent regulations

















Technical data			
Im system:	8930.0	Life Time LED 2:	100,000h - L80 - B10 (Ta 25C)
W system:	59.6	Voltage [Vin]:	230
Im source:	8930	Lamp code:	LED
W source:	55	Number of lamps for optical	1
Luminous efficiency (lm/W,	149.83	assembly:	
real value):		ZVEI Code:	LED
Im in emergency mode:	-	Number of optical	1
Total light flux at or above	0.0	assemblies:	
an angle of 90° [Lm]:		Intervallo temperatura	from -40°C to 35°C.
Light Output Ratio (L.O.R.)	100	ambiente:	
[%]:		Power factor:	See installation instructions
Beam angle [°]:	144° / 61°	Inrush current:	54 A / - μs
CRI:	70	Maximum number of	
Colour temperature [K]:	3000	luminaires of this type per miniature circuit breaker:	B10A: 7 luminaires B16A: 12 luminaires
MacAdam Step:	3		
Life Time LED 1:	100,000h - L90 - B10 (Ta 25C)		C10A: 12 luminaires C16A: 20 luminaires
		Minimum dimming %:	10
		Overvoltage protection:	0kV Common mode & 0kV Differential mode