


Last information update: September 2020

Product configuration: 3153+1639

3153: Projector with 75 W QR 111 dimmable electronic transformer



Product code

3153: Projector with 75 W QR 111 dimmable electronic transformer **Attention! Code no longer in production**

Technical description

Die-cast aluminium and thermoplastic suspended luminaire. The suspension system is made up of steel cables (L=2000) and provides simple mechanical anchoring. Rotation and inclination movements may be locked mechanically to guarantee precise positioning of the light beam - also during maintenance operations.

Installation

Ceiling mounted by means of the base provided.

Colour

Grey (15)

Weight (Kg)

1.68

Mounting

ceiling pendant


Wiring

Complete with dimmable electronic transformer for 75W 12V halogen lamps, inside the luminaire.

Notes

Complete with adjustable suspension cables and power-supply cable. The luminaire becomes IP40 with the use of accessory glasses. For the photometric data of the luminaire, refer to the photometric characteristics of the light source.

Complies with EN60598-1 and pertinent regulations



Technical data

Im system:	796	Colour temperature [K]:	3000
W system:	82	Lamp maximum intensity	1700
Im source:	796	[cd]:	
W source:	75	Ballast losses [W]:	7
Luminous efficiency (lm/W, 9,7 real value):		Voltage [Vin]:	12
Im in emergency mode:	-	Lamp code:	1639
Total light flux at or above an angle of 90° [Lm]:	0	Socket:	G53
Light Output Ratio (L.O.R.) [%]:	100	Number of lamps for optical assembly:	1
Beam angle [°]:	42°	ZVEI Code:	QR 111
CRI:	100	Number of optical assemblies:	1

Polar

