

Deep Frame


Design iGuzzini

iGuzzini

Last information update: October 2023

Product configuration: P921

P921: Deep Frame - 1 element - CoB warm LED - flood beam - dimmable DALI



Product code

P921: Deep Frame - 1 element - CoB warm LED - flood beam - dimmable DALI **Attention! Code no longer in production**

Technical description

Individual recessed luminaire for LED lamp. Version with a perimeter frame. Shaped sheet steel structural frame. Die-cast aluminium, twin swivel universal joint located in a position set back from the installation surface to guarantee a high level of visual comfort. Tilts $\pm 30^\circ$ around both the horizontal and vertical axes. Die-cast aluminium lighting body designed to optimise heat dispersal. High efficiency aluminium reflector - flood angle. High color rendering index, warm white LED lamp. Glass cover Mechanical installation system. DALI dimmable control gear unit included.

Installation

Recessed in 1 to 30mm thick false ceilings - secured with manually adjustable metal brackets. Preparation hole 167 x 167.

Colour

White (01) | Grey / Black (74)

Weight (Kg)

1.5

Mounting

ceiling recessed

Wiring

Complete with DALI dimmable control gear unit connected to the luminaire. Wiring for connecting to mains network on driver terminal board

Notes

Accessories available: refractor for elliptical flow distribution.

Complies with EN60598-1 and pertinent regulations



IP20

IP23

On the visible part of the product once installed



Technical data

lm system:	2477	Colour temperature [K]:	3000
W system:	32.2	MacAdam Step:	3
lm source:	3100	Life Time LED 1:	> 50,000h - L80 - B10 (Ta 25°C)
W source:	27	Ballast losses [W]:	5.2
Luminous efficiency (lm/W, real value):	76.9	Lamp code:	LED
lm in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	80	Number of optical assemblies:	1
Beam angle [°]:	38°	Control:	DALI
CRI:	90		


Polar

	CIE			
	nL 0.80			
	99-100-100-100-80			
	UGR 12.2-12.2			
	DIN A.61			
	UTE			
	0.80A+0.00T			
	F*1=987			
	F*1+F*2=998			
	F*1+F*2+F*3=1000			
	CIBSE			
	LG3 L<1500 cd/m² at 65°			
	UGR<16 L<1500 cd/mq @65°			
	Lux			
	h	d	Em	Emax
	2	1.4	1052	1298
	4	2.8	263	325
	6	4.1	117	144
	8	5.5	66	81

Utilisation factors

R	77	75	73	71	55	53	33	00	DRR
K0.8	72	68	65	63	67	65	64	62	78
1.0	75	72	69	67	71	69	68	66	82
1.5	79	76	74	73	75	73	73	70	88
2.0	81	79	78	77	78	77	76	74	92
2.5	83	81	80	79	80	79	78	76	95
3.0	84	83	82	81	82	81	80	78	97
4.0	85	84	84	83	83	82	81	79	99
5.0	85	85	84	84	83	83	82	80	100

Luminance curve limit



UGR diagram

Corrected UGR values (at 3100 lm bare lamp luminous flux)											
Reflect.: ceiling/cav walls work pl. Room dim x y		0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30
		0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30
		0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
		viewed crosswise					viewed endwise				
2H	2H	12.8	13.4	13.1	13.7	13.9	12.8	13.4	13.1	13.7	13.9
	3H	12.7	13.2	13.0	13.5	13.8	12.7	13.2	13.0	13.5	13.8
	4H	12.6	13.1	12.9	13.4	13.7	12.6	13.1	12.9	13.4	13.7
	6H	12.5	13.0	12.9	13.3	13.6	12.5	13.0	12.9	13.3	13.6
	8H	12.5	13.0	12.9	13.3	13.6	12.5	13.0	12.9	13.3	13.6
	12H	12.5	12.9	12.8	13.2	13.6	12.5	12.9	12.8	13.2	13.6
4H	2H	12.6	13.1	12.9	13.4	13.7	12.6	13.1	12.9	13.4	13.7
	3H	12.5	12.9	12.8	13.2	13.6	12.5	12.9	12.8	13.2	13.6
	4H	12.4	12.8	12.8	13.1	13.5	12.4	12.8	12.8	13.1	13.5
	6H	12.3	12.6	12.7	13.0	13.4	12.3	12.6	12.7	13.0	13.4
	8H	12.2	12.6	12.7	13.0	13.4	12.2	12.6	12.7	13.0	13.4
	12H	12.2	12.5	12.7	12.9	13.4	12.2	12.5	12.7	12.9	13.4
8H	4H	12.2	12.6	12.7	13.0	13.4	12.2	12.6	12.7	13.0	13.4
	6H	12.2	12.4	12.6	12.9	13.3	12.2	12.4	12.6	12.9	13.3
	8H	12.1	12.3	12.6	12.8	13.3	12.1	12.3	12.6	12.8	13.3
	12H	12.1	12.2	12.6	12.7	13.2	12.1	12.2	12.6	12.7	13.2
12H	4H	12.2	12.5	12.7	12.9	13.4	12.2	12.5	12.7	12.9	13.4
	6H	12.1	12.3	12.6	12.8	13.3	12.1	12.3	12.6	12.8	13.3
	8H	12.1	12.2	12.6	12.7	13.2	12.1	12.2	12.6	12.7	13.2
Variations with the observer position at spacing:											
S =	1.0H	5.7 / -12.8					5.7 / -12.8				
	1.5H	8.5 / -14.7					8.5 / -14.7				
	2.0H	10.5 / -17.4					10.5 / -17.4				