

iN60 Evo Stand-alone

Design iGuzzini

iGuzzini

Last information update: July 2025

Product configuration: RY88.L2

RY88.L2: Pendant-mounted Stand Alone - Led - Up/Down - DALI - GL - HO - Opal - L=1200 - 40W 5572.5lm - 3500K - White / Opal White

Product code

RY88.L2: Pendant-mounted Stand Alone - Led - Up/Down - DALI - GL - HO - Opal - L=1200 - 40W 5572.5lm - 3500K - White / Opal White

Technical description

Stand Alone pendant-mounted luminaire. The product consists of an extruded aluminium profile with zamak end caps. 3500K LED plate with direct (Down) and indirect (Up) light emission. High Output (HO) version for General Light profiles. The module optic and structural fittings combined with the use of a "Furukawa" flow recovery unit allow high system efficiency values to be achieved. DALI dimmable power supply integrated in the luminaire. For indirect light (Up), we supply an extruded aluminium support plate that is painted white to increase reflection. Opal PMMA diffuser screen. Pendant and power supply cables L=1500

Installation

Pendant-mounted

Colour

White / Opal White (L2)

Complies with EN60598-1 and pertinent regulations



Technical data

lm system:	5573	Colour temperature [K]:	3500
W system:	40	MacAdam Step:	3
lm source:	7430	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
W source:	36	Lamp code:	LED
Luminous efficiency (lm/W, real value):	139.3	Number of lamps for optical assembly:	1
lm in emergency mode:	-	ZVEI Code:	LED
Total light flux at or above an angle of 90° [Lm]:	2253	Number of optical assemblies:	1
Light Output Ratio (L.O.R.) [%]:	75	Control:	DALI-2
CRI (minimum):	80		

Polar

