


Last information update: February 2025

Product configuration: Q514

Q514: Frame 15 cells - Flood beam - LED



Product code

Q514: Frame 15 cells - Flood beam - LED

Technical description

Linear miniaturised recessed luminaire with 15 optical elements for LED lamps - fixed optics. Despite the ultracompact size of the product, the patented technology of the optic system guarantees an efficient flow and a high level of controlled glare visual comfort. Main body with die-cast aluminium radiant surface, version with perimeter surface frame. Metallised, thermoplastic, high definition Opti Beam reflectors, integrated in a set-back position in the anti-glare screen. Supplied with DALI power supply unit connected to the luminaire.

Installation

Recessed with steel wire springs for false ceilings from 1 to 25 mm thick - preparation hole 24 x 276.

Colour

White (01) | Black / Black (43) | Black / White (47) | White/Gold (41)* | Grey / Black (74)* | White / burnished chrome (E7)*

Weight (Kg)

0.75

* Colours on request


Mounting

wall recessed|ceiling recessed

Wiring

On the power supply unit with terminal board included.

Complies with EN60598-1 and pertinent regulations



Technical data

Im system:	2739	Colour temperature [K]:	4000
W system:	33.8	MacAdam Step:	2
Im source:	3300	Life Time LED 1:	> 50,000h - L80 - B10 (Ta 25°C)
W source:	30	Voltage [Vin]:	230
Luminous efficiency (Im/W, real value):	81	Lamp code:	LED
Im in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	83	Number of optical assemblies:	1
Beam angle [°]:	43°	Control:	DALI-2
CRI (minimum):	90		


Polar

<p>Imax=5625 cd α=42°</p>	CIE nL 0.83 100-100-100-100-83 UGR <10-<10	Lux			
	DIN A.61	h	d	Em	Emax
	UTE 0.83A+0.00T F*1=999 F*1+F*2=1000 F*1+F*2+F*3=1000	2	1.5	1145	1396
	CIBSE LG3 L<1500 cd/m² at 65° UGR<10 L<1500 cd/mq @65°	4	3.1	286	349
		6	4.6	127	155
	8	6.1	72	87	

Utilisation factors

R	77	75	73	71	55	53	33	00	DRR
K0.8	75	71	68	66	70	68	68	65	78
1.0	78	75	72	70	74	72	71	69	83
1.5	82	80	77	76	79	77	76	74	89
2.0	85	83	81	80	82	80	79	77	93
2.5	86	85	84	83	84	83	82	79	96
3.0	87	86	85	85	85	84	83	81	98
4.0	88	87	87	86	86	86	84	82	99
5.0	89	88	88	88	87	87	85	83	100

Luminance curve limit



UGR diagram

Corrected UGR values (at 3300 lm bare lamp luminous flux)											
Reflect.:		viewed crosswise					viewed endwise				
ceiling	cav	0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30
walls		0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30
work pl.		0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
Room dim											
x	y										
2H	2H	7.8	8.3	8.1	8.5	8.8	7.8	8.3	8.1	8.5	8.8
	3H	7.7	8.1	8.0	8.4	8.7	7.7	8.1	8.0	8.4	8.7
	4H	7.6	8.1	8.0	8.3	8.6	7.6	8.0	8.0	8.3	8.6
	6H	7.6	7.9	7.9	8.3	8.6	7.6	7.9	7.9	8.2	8.6
	8H	7.5	7.9	7.9	8.2	8.6	7.5	7.9	7.9	8.2	8.5
	12H	7.5	7.9	7.9	8.2	8.5	7.5	7.8	7.9	8.2	8.5
4H	2H	7.6	8.0	8.0	8.3	8.6	7.6	8.1	8.0	8.3	8.6
	3H	7.5	7.8	7.9	8.2	8.5	7.5	7.8	7.9	8.2	8.5
	4H	7.4	7.7	7.8	8.1	8.5	7.4	7.7	7.8	8.1	8.5
	6H	7.3	7.6	7.7	8.0	8.4	7.3	7.6	7.7	8.0	8.4
	8H	7.3	7.5	7.7	7.9	8.4	7.3	7.5	7.7	7.9	8.4
	12H	7.2	7.5	7.7	7.9	8.3	7.2	7.4	7.7	7.9	8.3
8H	4H	7.3	7.5	7.7	7.9	8.4	7.3	7.5	7.7	7.9	8.4
	6H	7.2	7.4	7.6	7.8	8.3	7.2	7.4	7.7	7.8	8.3
	8H	7.1	7.3	7.6	7.8	8.3	7.1	7.3	7.6	7.8	8.3
	12H	7.1	7.2	7.6	7.7	8.3	7.1	7.2	7.6	7.7	8.2
12H	4H	7.2	7.4	7.7	7.9	8.3	7.2	7.5	7.7	7.9	8.3
	6H	7.1	7.3	7.6	7.8	8.3	7.1	7.3	7.6	7.8	8.3
	8H	7.1	7.2	7.6	7.7	8.2	7.1	7.2	7.6	7.7	8.3
Variations with the observer position at spacing:											
S =	1.0H	7.0 / -14.5					7.0 / -14.5				
	1.5H	9.8 / -14.7					9.8 / -14.7				
	2.0H	11.8 / -14.8					11.8 / -14.8				