


Last information update: May 2024

Product configuration: N356

N356: spotlight - warm white - wide flood optic



Product code

N356: spotlight - warm white - wide flood optic **Attention! Code no longer in production**

Technical description

Adjustable spotlight with adapter for installation on mains voltage track for high-performance LED source with CoB technology, monochromatic Warm White (3000K) CRI90 emission. Electronic control gear housed inside the track-mounted power supply box. The luminaire is made of die-cast aluminium and thermoplastic. OPTIBEAM superpure aluminium reflector with high luminous efficacy and uniform distribution, wide flood optic. Features 90° inclination on the horizontal plane and 360° rotation around the vertical axis, with mechanical locking device for aiming. Passive cooling system. Possibility of installing a refractor, to be ordered separately, for elliptical light beam distribution.

Installation

The luminaire can be installed on a standard electrified track or on an appropriate channel incorporating an electrified track.

Colour

White (01) | Black (04)

Weight (Kg)

1.12

Mounting

three circuit track|ceiling surface

Wiring

product inclusive of electronic components incorporated into the track-mounted box.


Complies with EN60598-1 and pertinent regulations



Technical data

Im system:	2278	CRI:	90
W system:	29.3	Colour temperature [K]:	3000
Im source:	3000	MacAdam Step:	2
W source:	25	Life Time LED 1:	> 50,000h - L80 - B10 (Ta 25°C)
Luminous efficiency (Im/W, real value):	77.8	Lamp code:	LED
Im in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	76	Number of optical assemblies:	1
Beam angle [°]:	54°		


Polar

	Lux			
	h	d	Em	Emax
	2	2	582	738
	4	4.1	146	184
	6	6.1	65	82
	8	8.2	36	46

Utilisation factors

R	77	75	73	71	55	53	33	00	DRR
K0.8	68	64	61	59	63	61	61	58	77
1.0	71	68	65	63	67	65	64	62	81
1.5	75	72	70	69	71	70	69	66	88
2.0	77	75	74	73	74	73	72	70	92
2.5	79	77	76	75	76	75	74	72	95
3.0	80	79	78	77	77	77	76	74	97
4.0	80	80	79	79	78	78	77	75	99
5.0	81	80	80	80	79	79	78	76	100

Luminance curve limit



UGR diagram

Corrected UGR values (at 3000 lm bare lamp luminous flux)											
Reflect.: ceiling walls work pl. Room dim x y		viewed crosswise					viewed endwise				
2H	2H	20.8	21.5	21.1	21.7	21.9	20.8	21.5	21.1	21.7	21.9
	3H	20.7	21.3	21.0	21.5	21.8	20.7	21.3	21.0	21.5	21.8
	4H	20.6	21.1	21.0	21.4	21.7	20.6	21.1	21.0	21.4	21.7
	6H	20.5	21.0	20.9	21.3	21.7	20.5	21.0	20.9	21.3	21.7
	8H	20.5	21.0	20.9	21.3	21.6	20.5	21.0	20.9	21.3	21.6
	12H	20.5	20.9	20.8	21.2	21.6	20.5	20.9	20.8	21.2	21.6
4H	2H	20.6	21.1	21.0	21.4	21.7	20.6	21.1	21.0	21.4	21.7
	3H	20.5	20.9	20.8	21.2	21.6	20.5	20.9	20.8	21.2	21.6
	4H	20.4	20.8	20.8	21.1	21.5	20.4	20.8	20.8	21.1	21.5
	6H	20.3	20.6	20.7	21.0	21.4	20.3	20.6	20.7	21.0	21.4
	8H	20.2	20.6	20.7	21.0	21.4	20.2	20.6	20.7	21.0	21.4
	12H	20.2	20.5	20.7	20.9	21.4	20.2	20.5	20.7	20.9	21.4
8H	4H	20.2	20.6	20.7	21.0	21.4	20.2	20.6	20.7	21.0	21.4
	6H	20.2	20.4	20.6	20.9	21.3	20.2	20.4	20.6	20.9	21.3
	8H	20.1	20.3	20.6	20.8	21.3	20.1	20.3	20.6	20.8	21.3
	12H	20.0	20.2	20.5	20.7	21.2	20.0	20.2	20.5	20.7	21.2
12H	4H	20.2	20.5	20.7	20.9	21.4	20.2	20.5	20.7	20.9	21.4
	6H	20.1	20.3	20.6	20.8	21.3	20.1	20.3	20.6	20.8	21.3
	8H	20.0	20.2	20.5	20.7	21.2	20.0	20.2	20.5	20.7	21.2
Variations with the observer position at spacing:											
S =	1.0H	5.3 / -17.5					5.3 / -17.5				
	1.5H	8.1 / -21.6					8.1 / -21.6				
	2.0H	10.1 / -25.1					10.1 / -25.1				