


Last information update: March 2025

Product configuration: RQ52.01

RQ52.01: Ø62mm body - dimmable electronic DALI - SuperSpot optic - 13.3W 627.8lm - 3000K - CRI 97 - White

**Product code**

RQ52.01: Ø62mm body - dimmable electronic DALI - SuperSpot optic - 13.3W 627.8lm - 3000K - CRI 97 - White

Technical description

Adjustable spotlight with adapter for installation on an electrified track. High chromatic yield LED lamp (CRI97) with 3000K tone and OptiBeam Lens optic system and SuperSpot optic. DALI dimmable electronic power supply integrated in product track adapter. Luminaire made of die-cast aluminium and thermoplastic material that allows a 360° rotation about the vertical axis and 90° tilting relative to the horizontal plane with mechanical aiming locks. Passive heat dissipation. Spotlight with "Push&Go" system designed to hold up to three flat accessories at the same time. The same system can also be used to apply another external component selected from the directional flaps and anti-glare screen. All internal accessories rotate 360° about the spotlight longitudinal axis.

Installation

Installation on an electrified track.

Colour

White (01)

Weight (Kg)

0.51

Mounting

wall surface/ceiling surface

Wiring


Electronic components integrated in product.

Complies with EN60598-1 and pertinent regulations



IP20

IP40

for optical
assembly**Technical data**

lm system:	628	MacAdam Step:	2
W system:	13.3	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
lm source:	860	Lamp code:	LED
W source:	10	Number of lamps for optical assembly:	1
Luminous efficiency (lm/W, real value):	47.2	ZVEI Code:	LED
lm in emergency mode:	-	Number of optical assemblies:	1
Total light flux at or above an angle of 90° [Lm]:	0	Power factor:	See installation instructions
Light Output Ratio (L.O.R.) [%]:	73	Inrush current:	5 A / 50 µs
Beam angle [°]:	10°	Maximum number of luminaires of this type per miniature circuit breaker:	B10A: 31 luminaires B16A: 50 luminaires C10A: 52 luminaires C16A: 85 luminaires
CRI (minimum):	97	Overvoltage protection:	4kV Common mode & 2kV Differential mode
Colour temperature [K]:	3000	Control:	DALI-2

Polar

Imax=14950 cd		Lux			
h	d	Em	Emax		
2	0.3	2975	3736		
4	0.7	744	934		
6	1	331	415		
8	1.3	186	233		

 $\alpha = 10^\circ$