iGuzzini

Last information update: October 2024

Product configuration: RC01

RC01: Neutral white medium body spotlight - Bluetooth - Medium optic



Product code

RC01: Neutral white medium body spotlight - Bluetooth - Medium optic

Technical description

Adjustable spotlight with adapter for installation on a mains voltage track. Luminaire made of die-cast aluminium. Spotlight double adjustability allows a 360° rotation about the vertical axis and 90° tilting relative to the horizontal plane. Mechanical aiming locks for rotation on both the vertical axis and horizontal plane. Optical assembly made up of Neutral White 4000 K, high colour rendering CRI 97, C.o.B LEDs. Luminaire with Bluetooth Low Energy technology (Casambi). Frequency 2.4 GHz. The luminaire can be controlled with the Casambi system app and components that enable on-off, dimming and scene recall functions. The app is available on the Apple Store and Google Play Store. It can be integrated in the system's "Mesh" network that allows multiple luminaires to be controlled. OTA (over the air) update via app. Integrated Beacon that can be activated via an app (iBeacon) that enables smart functions for third party applications.


Weight (Kg)

2.1

Installation

Electrified track or base-mounted. Max luminaire-luminaire distance (*): 8 m; max smartphone-luminaire distance (*): 20 m.

Colour White (01) | Black (04)



Mounting

dali track|three circuit track|wall surface|ceiling surface

Wiring

Luminaire that can be controlled with Bluetooth technology (Casambi)

Notes

(*) The maximum distance is affected by physical obstacles, like walls, metal panels and the layout of the system. We suggest that a test is conducted at the installation site.

Complies with EN60598-1 and pertinent regulations







97







Technical data Im system: 3072 Colour temperature [K]: 4000 W system: 39.2 MacAdam Step: Life Time LED 1: > 50,000h - L90 - B10 (Ta 25°C) 3950 Im source: W source: 36 Lamp code: LED Number of lamps for optical 1 Luminous efficiency (lm/W, 78.4 real value): assembly: ZVEI Code: LED Im in emergency mode: Total light flux at or above 0 Number of optical an angle of 90° [Lm]: assemblies:

Light Output Ratio (L.O.R.) 78 Power factor: See installation instructions Control: Bluetooth Casambi Beam angle [°]: 18°

Polar

[%]:

CRI (minimum):

Imax=20484 cd	Lux			
90° 180° 90°	h	d	Em	Emax
	2	0.6	3860	5121
	4	1.2	965	1280
20000	6	1.8	429	569
α=17°	8	2.4	241	320