



Last information update: April 2024

Product configuration: 5243

5243: Ceiling luminaire with emergency device and inductive control gear 2x36 W TC-L



Product code

5243: Ceiling luminaire with emergency device and inductive control gear 2x36 W TC-L **Attention! Code no longer in production**

Technical description

Ceiling luminaire for internal lighting using 2x36W TC-L compact fluorescent lamps with separate switching. Made up of a support in sheet steel for the control gear. A methacrylate diffuser is hooked to the support by means of fixing elements located on the diffuser perimeter.

Installation

Fixed to the wall or the ceiling with fischer screws.

Colour

White (01)

Weight (Kg)

5.3

Mounting

wall surface|ceiling surface

Wiring

Wiring for 2x36W TC-L compact fluorescent lamp with electronic control gear and inverter.

Notes

The flow data refer to one light source.

Complies with EN60598-1 and pertinent regulations



Technical data

Im system:	3134.32	CRI:	85
W system:	90.0	Colour temperature [K]:	2700
Im source:	5800	Voltage [Vin]:	230
W source:	36	Lamp code:	1739
Luminous efficiency (Im/W, real value):	34.83	Socket:	2G11
Im in emergency mode:	-	Number of lamps for optical assembly:	2
Total light flux at or above an angle of 90° [Lm]:	4.7	ZVEI Code:	TC-L
Light Output Ratio (L.O.R.) [%]:	54	Number of optical assemblies:	1
Beam angle [°]:	122°		