


Last information update: May 2024

Product configuration: MQ03

MQ03: Large body spotlight - warm white - electronic ballast - medium optic

**Product code**MQ03: Large body spotlight - warm white - electronic ballast - medium optic **Attention! Code no longer in production****Technical description**

Pendant luminaire equipped with a multiphase adapter made of die-cast aluminium and thermoplastic material. The pendant system consists of steel cables L=2000 that provide a simple mechanical anchoring system. Having been rotated and tilted, the luminaire can be locked mechanically in position to ensure efficient light aiming (even during maintenance operations). Luminaire for high output LED lamp with monochrome emission in a warm white colour tone (3000K). Electronic ballast. Equipped with an accessory holding ring designed to contain a flat accessory. Another external component can also be applied, selected from directional flaps and an asymmetric screen. All external accessories rotate 360° about the spotlight longitudinal axis.

Installation

Mounted on an electrified track with a multiphase adapter.

Colour

White (01) | Grey / Black (74)


Mounting

ceiling pendant

Wiring


Electronic components housed in the luminaire.

Complies with EN60598-1 and pertinent regulations

**Technical data**

lm system:	3244	CRI (minimum):	90
W system:	37.5	Colour temperature [K]:	3000
lm source:	4400	MacAdam Step:	2
W source:	33	Life Time LED 1:	> 50,000h - L80 - B10 (Ta 25°C)
Luminous efficiency (lm/W, real value):	86.5	Lamp code:	LED
lm in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	74	Number of optical assemblies:	1
Beam angle [°]:	16°		

Polar

Imax=25039 cd		Lux			
		h	d	Em	Emax
		2	0.6	4824	6260
		4	1.1	1206	1565
		6	1.7	536	696
		8	2.2	301	391
$\alpha=16^\circ$					