


Last information update: April 2025

**Product configuration: MQ30**

MQ30: Adjustable 15 - cell Recessed frame - LED - Warm white - DALI dimmable power supply - Flood Beam



**Product code**

MQ30: Adjustable 15 - cell Recessed frame - LED - Warm white - DALI dimmable power supply - Flood Beam

**Technical description**

Recessed rectangular luminaire with LEDs. Shaped steel sheet structural compartment with outer rim. The 15 lighting cells linear body, in die-cast aluminium, can be used to direct the emission with a tilting adjustability of +/- 30°. Metallised thermoplastic high definition optics, integrated in a rear position in the black anti-glare screen; the structure of the optical system prevents a pinpoint effect, allowing precise, circular light distribution and emission with controlled luminance. Supplied with DALI dimmable control gear connected to the luminaire. Warm white high chromatic yield LED.

**Installation**

recessed with mechanical blocking system for false ceilings from 1 to 25 mm; can be installed on ceilings and walls (vertical + horizontal) - preparation slot 80 x 428


**Colour**

Black / Black (43) | Black / White (47) | Grey / Black (74)\*

**Weight (Kg)**

2.06

\* Colours on request



**Mounting**

wall recessed|ceiling recessed

**Wiring**

on power box: screw connections

**Notes**

dimming function with pushbutton (TOUCH DIM/PUSH): for this option consult the instructions included in the package

Complies with EN60598-1 and pertinent regulations



**Technical data**

Im system:	2196.43	CRI:	95
W system:	35.0	Colour temperature [K]:	3000
Im source:	2750	MacAdam Step:	3
W source:	31	Life Time LED 1:	50,000h - L90 - B10 (Ta 25C)
Luminous efficiency (lm/W, real value):	62.76	Lamp code:	LED
Im in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0.0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	80	Number of optical assemblies:	1
Beam angle [°]:	31°	Control:	DALI-2