

iN60 Evo Stand-alone

Design iGuzzini

iGuzzini

Last information update: February 2025

Product configuration: RZ12.L2

RZ12.L2: Pendant-mounted Stand Alone LED - Up/Down - DALI - UGR<19 - LO - MPO - L=1200 - 13.6W 1814.4lm - 3500K - White / Opal White



Product code

RZ12.L2: Pendant-mounted Stand Alone LED - Up/Down - DALI - UGR<19 - LO - MPO - L=1200 - 13.6W 1814.4lm - 3500K - White / Opal White

Technical description

Stand Alone pendant-mounted luminaire. The product consists of an extruded aluminium profile with zamak end caps. 3500K LED plate with direct (Down) and indirect (Up) light emission. Low Output (LO) controlled luminance version ($L \leq 3000 \text{cd/m}^2$) ideal for environments with video monitors. The module optic and structural fittings allow high luminous flux and system efficiency values. DALI dimmable power supply integrated in the luminaire. Extruded aluminium heat sink and "Halogen Free" electric cables. For indirect light (Up), we supply an extruded aluminium support plate that is painted white to increase reflection. Microprismatic PMMA diffuser screen. Pendant and power supply cables L=1500


Installation

Pendant-mounted

Colour

White / Opal White (L2)

Complies with EN60598-1 and pertinent regulations



Technical data

| | | | |
|--|-------|---------------------------------------|---------------------------------|
| lm system: | 1814 | Colour temperature [K]: | 3500 |
| W system: | 13.6 | MacAdam Step: | 3 |
| lm source: | 2520 | Life Time LED 1: | > 50,000h - L90 - B10 (Ta 25°C) |
| W source: | 12 | Lamp code: | LED |
| Luminous efficiency (lm/W, real value): | 133.4 | Number of lamps for optical assembly: | 1 |
| lm in emergency mode: | - | ZVEI Code: | LED |
| Total light flux at or above an angle of 90° [Lm]: | 894 | Number of optical assemblies: | 1 |
| Light Output Ratio (L.O.R.) [%]: | 72 | Control: | DALI-2 |
| CRI (minimum): | 80 | | |

Polar

