

## Features




- Recessed installation in false ceilings with 1 to 35 mm.
- Galvanised, painted sheet steel supporting structure and end caps.
- Wall-washer versions with painted aluminium lamp cover and superpure aluminium reflector.
- UGR<19 Darklight versions, super-pure aluminium reflectors and lamellar optics with parabolic profile.
- General light versions with polycarbonate diffuser.
- Available electronic and DALI control gear and emergency with inverter; 1,5 hours autonomy with 12 hour recharging cycle - 3 hours autonomy with 24 hour recharging cycle. Conforms to EN60598-2-22.
- Multiwatt ballasts.
- High level of light output.
- Luminaire reduced height.



## Light distribution


### Darklight

Ideal when lighting offices and spaces with monitors. The ultrapure aluminium reflectors deliver top lighting performance and controlled luminance in compliance with EN 12464 1 standards.





### General light

The polycarbonate diffusing screens has a comfortable and homogenous light distribution with limited glare from the lamps.





### Wall Washer

Ideal for vertical surfaces. The shape of the reflector was specially designed, and it produces uniform lighting on walls.







## Recessed





100x(1174/1474xN+13)  
N=number of fittings

light source	W	length	code colour
T 16 (G5)	Wall washer		
	Electronic		
	28 W	1198	5800 01
	35 W	1498	5801 01
	54 W	1198	5802 01
	80 W	1498	5803 01
	DALI multiwatt		
	28/54 W	1198	5806 01
	35/49/80 W	1498	5807 01
	DALI versions occupy 1 address		



100x(1174/1474xN+13)  
N=number of fittings

light source	W	length	code colour
T 16 (G5)	Darklight		
	Electronic		
	35 W	1498	5814 01
	54 W	1198	5815 01
	2x35 W	1498	5816 01
	2x54 W	1198	5817 01
	DALI multiwatt		
	28/54 W	1198	5818 01
	2x35 W	1498	5819 01
	2x28/54 W	1198	5820 01
Electronic and permanent emergency light			
54 W	1198	5821 01	
DALI versions occupy 1 address			



100x(1174/1474xN+13)  
N=number of fittings

light source	W	length	code colour
T 16 (G5)	General light		
	Electronic		
	54 W	1198	5823 01
	80 W	1498	5824 01
	2x35 W	1498	5825 01
	2x54 W	1198	5826 01
	DALI		
	28/54 W	1198	5827 01
	35/49/80 W	1498	5828 01
	2x35 W	1498	5829 01
2x54 W	1198	5830 01	
Electronic and permanent emergency light			
54 W	1198	MM61 01	
2x35 W	1498	MM62 01	
DALI versions occupy 1 address			
Complete with protection screen			