



Last information update: May 2024

Product configuration: MS42

MS42: mini body LED warm white - spot optic

**Product code**MS42: mini body LED warm white - spot optic **Attention! Code no longer in production****Technical description**

Recessed luminaire made of die-cast aluminium and thermoplastic material, with high-performing Warm White LED with monochromatic emission. LED optic with plastic lenses with narrow beam . 335° rotation around vertical axis and 65° rotation around horizontal axis with continuous frictioning (only on horizontal axis). Anti-glare screen available as accessory. The technical characteristics of the luminaires comply with EN60598-1 norms and following amendments.

Installation

Recessed installation in false ceilings with thickness from 1 mm to 20 mm by means of special steel torsional springs and hinged brackets.

Colour

White (01) | Grey (15)

Mounting

ceiling recessed

Wiring

Electronic components for LED to be ordered separately.

Notes


For compliance with the NFC 20-455 standard use an optional filter code MW57 for each optical assembly

Complies with EN60598-1 and pertinent regulations

**Technical data**

lm system:	116	CRI (minimum):	80
W system:	1.8	Colour temperature [K]:	3000
lm source:	140	MacAdam Step:	3
W source:	1.8	Life Time LED 1:	> 50,000h - L80 - B10 (Ta 25°C)
Luminous efficiency (lm/W, real value):	64.6	Lamp code:	LED
lm in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	83	Number of optical assemblies:	1
Beam angle [°]:	12°	LED current [mA]:	600

Polar

Imax=1602 cd		Lux				
90°	180°	90°	h	d	Em	E _{max}
1500		0°	2	0.4	329	401
			4	0.8	82	100
			6	1.3	37	45
			8	1.7	21	25
$\alpha = 12^\circ$						

Utilisation factors

R	77	75	73	71	55	53	33	00	DRR
K0.8	75	71	68	66	70	68	68	65	78
1.0	78	75	72	70	74	72	71	69	83
1.5	82	79	77	76	78	77	76	73	89
2.0	85	83	81	80	82	80	79	77	93
2.5	86	85	84	83	84	82	82	79	96
3.0	87	86	85	85	85	84	83	81	98
4.0	88	87	87	86	86	86	84	82	99
5.0	89	88	88	88	87	86	85	83	100

Luminance curve limit

