


Last information update: May 2024

**Product configuration: 5031**

5031: Surface-mounted luminaire - Warm white - ON-OFF - diffused light

**Product code**5031: Surface-mounted luminaire - Warm white - ON-OFF - diffused light **Attention! Code no longer in production****Technical description**

Diffused light ceiling- / wall-mounted luminaire. LED lamps. Fixing plate made of shaped sheet steel which is painted white. Aluminium LED support acts as a heat sink. Opal PMMA diffuser screen - the shape and finish give uniform, comfortable light emission. Warm white high efficiency LED

**Installation**

Ceiling- or wall-mounted. Plate is fixed to surface using screws and screw anchors (not supplied). LED unit removable using easy-lock system. Thermoplastic screen manually fixed on plate with rotation springs.

**Colour**

White (01)

**Weight (Kg)**

2.11

**Mounting**

wall surface|ceiling surface

**Wiring**

quick-coupling terminal block on fixing plate; set up for pass-through wiring between two or more luminaires; quick-connector links control gear box and removable LED unit.

Complies with EN60598-1 and pertinent regulations

**Technical data**

lm system:	2058.0	CRI:	80
W system:	17.0	Colour temperature [K]:	3000
lm source:	2450	MacAdam Step:	3
W source:	15	Life Time LED 1:	> 50,000h - L80 - B10 (Ta 25C)
Luminous efficiency (lm/W, real value):	121.06	Lamp code:	LED
lm in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	126.98	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	84	Number of optical assemblies:	1
Beam angle [°]:	118°		