


Last information update: February 2025

Product configuration: R610

R610: Minimal section 3 x 5 LEDs - Wall Washer



Product code

R610: Minimal section 3 x 5 LEDs - Wall Washer

Technical description

Linear recessed miniaturised luminaire for LED lamps, specialised for vertical wall lighting. The patented optic system guarantees a homogeneous and effective emission on the wall, as well as avoiding shadow zones near the ceiling. Main body with die-cast aluminium radiant surface, minimal (frameless) version for mounting flush with the ceiling. For recessed installation in a false ceiling a specific adapter is required that is available with a separate item code. Flux enhancer - superpure aluminium reflector - asymmetrical textured PMMA screen - black polycarbonate internal perimeter frame. Supplied with a power supply unit connected to the luminaire.

Installation

The recess body is inserted in the specific adapter installed previously by means of a steel wire spring - check the thickness of the false ceiling and use a compatible frame available with a separate item code.

Colour

Black (04)

Weight (Kg)


0.86

Mounting

wall recessed|ceiling recessed

Wiring

on power supply box: screw connections.




Complies with EN60598-1 and pertinent regulations



Technical data

| | | | |
|--|------|---------------------------------------|---------------------------------|
| lm system: | 1220 | CRI (typical): | 92 |
| W system: | 33.6 | Colour temperature [K]: | 2700 |
| lm source: | 3050 | MacAdam Step: | 3 |
| W source: | 29 | Life Time LED 1: | > 50,000h - L90 - B10 (Ta 25°C) |
| Luminous efficiency (lm/W, real value): | 36.3 | Lamp code: | LED |
| lm in emergency mode: | - | Number of lamps for optical assembly: | 1 |
| Total light flux at or above an angle of 90° [Lm]: | 0 | ZVEI Code: | LED |
| Light Output Ratio (L.O.R.) [%]: | 40 | Number of optical assemblies: | 1 |
| CRI (minimum): | 90 | Control: | DALI-2 |

Polar



Illuminances

Lux Wall distance = 1m

| | | | | | | | | | | | |
|---|---|----|----|----|-----|-----|-----|----|----|----|---|
| 3 | 3 | 7 | 16 | 42 | 125 | 226 | 125 | 42 | 16 | 7 | 3 |
| 2 | 5 | 11 | 22 | 53 | 120 | 169 | 120 | 53 | 22 | 11 | 5 |
| 1 | 6 | 11 | 23 | 52 | 97 | 123 | 97 | 52 | 23 | 11 | 6 |
| 0 | 6 | 11 | 19 | 32 | 44 | 50 | 44 | 32 | 19 | 11 | 6 |
| | m | -2 | -1 | 0 | 1 | 2 | 3 | | | | |