


Last information update: October 2024



Product code

2314: Recessed frame - LED - Neutral white - Integrated Electronic control gear - Wall washer optic

Technical description

Miniaturized recessed rectangular luminaire with LEDs. Main body with die-cast aluminium radiant surface, version with perimeter surface frame. Asymmetrical optic system designed to achieve an effective wall washer distribution. Flux enhancer - superpure aluminium reflector - screen in PMMA with ribbed texture; a special film in acrylic material, combined with the screen, allow for a uniform and effective light emission on the wall. Black polycarbonate internal perimeter frame. Supplied with electronic control gear connected to the luminaire. Neutral white LED.

Installation

recessed with steel springs for false ceilings from 1 to 25 mm; can be installed on ceilings and walls (vertical + horizontal) - preparation slot 37 x 141. To light the wall correctly check the installation distances and centre-to-centre distances on the instructions sheet.

Colour

Black / Black (43) | Black / White (47)

Weight (Kg)

0.3

Mounting

wall recessed|ceiling recessed


Wiring

on power box: screw connections

Notes

accessory anti-glare screen available code MPX7

Complies with EN60598-1 and pertinent regulations



On the visible part of the product once installed

Technical data

lm system:	-	CRI:	90
W system:	10 (*)	Colour temperature [K]:	4000
lm source:	-	Number of lamps for optical assembly:	1
W source:	10 (*)	ZVEI Code:	LED
lm in emergency mode:	-	Number of optical assemblies:	1
Beam angle [°]:	50° / 63° (*)		