


Last information update: October 2024

Product configuration: QQ52

QQ52: Square, Frameless, Recessed luminaire - Warm white LED - Flood optic



Product code

QQ52: Square, Frameless, Recessed luminaire - Warm white LED - Flood optic

Technical description

square, miniaturised, recessed luminaire for an individual LED - fixed optic - flood beam angle. Die-cast aluminium body, minimal version (frameless). Metallised, thermoplastic, high definition optic, integrated in a rear position in the black, anti-glare screen. Connecting cable supplied. Ballast not included, available with separate code. High CRI, warm white LED.

Installation

recessed with steel wire springs on the specific adapter (included) which allows flush-mounting with the ceiling. Adapter for fitting luminaire to false ceilings (12.5 mm thick) with self-tapping screws; subsequent filling and smoothing operations; insertion of luminaire body and stylish finishing. Preparation hole 64 x 35

Colour

White (01) | Black (04)


Mounting

wall recessed|ceiling recessed|ceiling surface

Wiring

Direct current ballasts to be ordered separately: electronic (MXF9) for max. 7 LEDs; 0-10V dimmable (Y360) for max. 18 LEDs; DALI dimmable (BZM4) for max. 15 LEDs (check instruction leaflet for compatible lengths of cables to be used)

Complies with EN60598-1 and pertinent regulations




On the visible part of the product once installed

Technical data

lm system:	383	CRI (typical):	92
W system:	3.9	Colour temperature [K]:	3000
lm source:	450	MacAdam Step:	3
W source:	3.9	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
Luminous efficiency (lm/W, real value):	98.1	Lamp code:	LED
lm in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	85	Number of optical assemblies:	1
Beam angle [°]:	32°	LED current [mA]:	700
CRI (minimum):	90	Control:	DALI-2

Polar



Utilisation factors

R	77	75	73	71	55	53	33	00	DRR
K0.8	77	73	70	68	72	70	69	67	78
1.0	80	77	74	72	76	74	73	71	83
1.5	84	81	79	78	80	79	78	75	89
2.0	87	85	83	82	84	82	81	79	93
2.5	88	87	86	85	86	85	84	81	96
3.0	89	88	88	87	87	86	85	83	98
4.0	90	90	89	89	88	88	87	84	99
5.0	91	90	90	90	89	89	87	85	100

UGR diagram

Corrected UGR values (at 450 lm bare lamp luminous flux)											
Reflect.:		viewed crosswise					viewed endwise				
ceiling/cav		0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30
walls		0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30
work pl.		0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
Room dim		viewed crosswise					viewed endwise				
x	y										
2H	2H	-2.8	-2.2	-2.5	-2.0	-1.8	-2.8	-2.2	-2.5	-2.0	-1.8
	3H	-2.9	-2.4	-2.6	-2.1	-1.9	-2.9	-2.4	-2.6	-2.1	-1.9
	4H	-3.0	-2.5	-2.6	-2.2	-1.9	-3.0	-2.5	-2.6	-2.2	-1.9
	6H	-3.0	-2.6	-2.7	-2.3	-2.0	-3.0	-2.6	-2.7	-2.3	-2.0
	8H	-3.1	-2.7	-2.7	-2.4	-2.0	-3.1	-2.7	-2.7	-2.4	-2.0
	12H	-3.1	-2.7	-2.7	-2.4	-2.0	-3.1	-2.7	-2.7	-2.4	-2.0
4H	2H	-3.0	-2.5	-2.6	-2.2	-1.9	-3.0	-2.5	-2.6	-2.2	-1.9
	3H	-3.1	-2.7	-2.7	-2.4	-2.0	-3.1	-2.7	-2.7	-2.4	-2.0
	4H	-3.2	-2.9	-2.8	-2.5	-2.1	-3.2	-2.9	-2.8	-2.5	-2.1
	6H	-3.3	-3.0	-2.9	-2.6	-2.2	-3.3	-3.0	-2.9	-2.6	-2.2
	8H	-3.3	-3.1	-2.9	-2.7	-2.2	-3.3	-3.1	-2.9	-2.7	-2.2
	12H	-3.4	-3.1	-2.9	-2.7	-2.3	-3.4	-3.1	-2.9	-2.7	-2.3
8H	4H	-3.3	-3.1	-2.9	-2.7	-2.2	-3.3	-3.1	-2.9	-2.7	-2.2
	6H	-3.4	-3.2	-3.0	-2.8	-2.3	-3.4	-3.2	-3.0	-2.8	-2.3
	8H	-3.5	-3.3	-3.0	-2.8	-2.3	-3.5	-3.3	-3.0	-2.8	-2.3
	12H	-3.5	-3.4	-3.0	-2.9	-2.4	-3.5	-3.4	-3.0	-2.9	-2.4
12H	4H	-3.4	-3.1	-2.9	-2.7	-2.3	-3.4	-3.1	-2.9	-2.7	-2.3
	6H	-3.5	-3.3	-3.0	-2.8	-2.3	-3.5	-3.3	-3.0	-2.8	-2.3
	8H	-3.5	-3.4	-3.0	-2.9	-2.4	-3.5	-3.4	-3.0	-2.9	-2.4
Variations with the observer position at spacing:											
S =	1.0H	0.9 / -25.5					0.9 / -25.5				
	1.5H	9.7 / -26.0					9.7 / -26.0				
	2.0H	11.7 / -26.8					11.7 / -26.8				