



Last information update: April 2024

**Product configuration: N022**

N022: Fixed circular recessed luminaire - Ø242 mm - neutral white - wide flood optic - UGR&lt;19

**Product code**

N022: Fixed circular recessed luminaire - Ø242 mm - neutral white - wide flood optic - UGR&lt;19

**Technical description**

Fixed round luminaire designed to use a LED lamp with C.O.B. technology. Version with rim for surface-mounting. Reflector vacuum-metallised with aluminium vapours with an anti-scratch protective layer. Structure with die-cast aluminium perimeter frame, black, zinc-plated sheet steel brackets and extruded aluminium dissipater painted black. Passive dissipation system. Product complete with LED lamp in neutral white colour tone (3000K). General light emission, with controlled luminance UGR<19 1500 cd/m<sup>2</sup> α<65° wide flood optic.

**Installation**

Recessed using torsion springs which allow easy installation in false ceilings with thickness ranging from 1 mm to 25 mm.

**Colour**

White / Aluminium (39)

**Weight (Kg)**

2.46

**Mounting**

ceiling recessed

**Wiring**

product complete with DALI components

Complies with EN60598-1 and pertinent regulations




IP20

IP23

On the visible part of the product once installed

**Technical data**


lm system:	6309	Life Time LED 1:	> 50,000h - L80 - B10 (Ta 25°C)
W system:	55.4	Lamp code:	LED
lm source:	8200	Number of lamps for optical assembly:	1
W source:	49	ZVEI Code:	LED
Luminous efficiency (lm/W, real value):	113.9	Number of optical assemblies:	1
lm in emergency mode:	-	Power factor:	See installation instructions
Total light flux at or above an angle of 90° [Lm]:	0	Inrush current:	30 A / 200 µs
Light Output Ratio (L.O.R.) [%]:	77	Maximum number of luminaires of this type per miniature circuit breaker:	B10A: 12 luminaires B16A: 20 luminaires C10A: 20 luminaires C16A: 34 luminaires
Beam angle [°]:	58°	Minimum dimming %:	1
CRI (minimum):	80	Overvoltage protection:	2kV Common mode & 2kV Differential mode
Colour temperature [K]:	4000	Control:	DALI-2
MacAdam Step:	2		

**Polar**

# Utilisation factors

R	77	75	73	71	55	53	33	00	DRR
K0.8	70	66	63	61	65	63	63	60	78
1.0	73	69	67	65	69	66	66	64	83
1.5	76	74	72	70	73	71	70	68	89
2.0	78	77	75	74	76	74	74	71	93
2.5	80	79	78	77	77	77	76	74	96
3.0	81	80	79	78	79	78	77	75	98
4.0	82	81	81	80	80	79	78	76	99
5.0	82	82	81	81	81	80	79	77	100

# Luminance curve limit



# UGR diagram

Corrected UGR values (at 8200 lm bare lamp luminous flux)											
Reflect.: ceiling walls work pl. Room dim x y		viewed crosswise					viewed endwise				
2H	2H	14.9	15.5	15.1	15.7	15.9	14.9	15.5	15.1	15.7	15.9
	3H	14.7	15.3	15.0	15.5	15.8	14.7	15.3	15.0	15.5	15.8
	4H	14.7	15.2	15.0	15.4	15.7	14.7	15.2	15.0	15.4	15.7
	6H	14.6	15.0	14.9	15.3	15.7	14.6	15.0	14.9	15.3	15.7
	8H	14.5	15.0	14.9	15.3	15.6	14.5	15.0	14.9	15.3	15.6
	12H	14.5	14.9	14.9	15.3	15.6	14.5	14.9	14.9	15.3	15.6
4H	2H	14.7	15.2	15.0	15.4	15.7	14.7	15.2	15.0	15.4	15.7
	3H	14.5	14.9	14.9	15.3	15.6	14.5	14.9	14.9	15.3	15.6
	4H	14.4	14.8	14.8	15.2	15.5	14.4	14.8	14.8	15.2	15.5
	6H	14.3	14.6	14.7	15.0	15.5	14.3	14.6	14.7	15.0	15.5
	8H	14.3	14.6	14.7	15.0	15.4	14.3	14.6	14.7	15.0	15.4
	12H	14.2	14.5	14.7	14.9	15.4	14.2	14.5	14.7	14.9	15.4
8H	4H	14.3	14.6	14.7	15.0	15.4	14.3	14.6	14.7	15.0	15.4
	6H	14.2	14.4	14.6	14.9	15.3	14.2	14.4	14.6	14.9	15.3
	8H	14.1	14.3	14.6	14.8	15.3	14.1	14.3	14.6	14.8	15.3
	12H	14.1	14.3	14.6	14.7	15.3	14.1	14.3	14.6	14.7	15.3
12H	4H	14.2	14.5	14.7	14.9	15.4	14.2	14.5	14.7	14.9	15.4
	6H	14.1	14.3	14.6	14.8	15.3	14.1	14.3	14.6	14.8	15.3
	8H	14.1	14.3	14.6	14.7	15.3	14.1	14.3	14.6	14.7	15.3
Variations with the observer position at spacing:											
S =	1.0H	6.5 / -24.8					6.5 / -24.8				
	1.5H	9.4 / -25.4					9.4 / -25.4				
	2.0H	11.4 / -25.8					11.4 / -25.8				