

**Dimmable electronic power supply unit DALI/Step-Dim/Middle of the night profile IP20 75W - VIN = 220-240VAC 50/60Hz Iout =350mA**

Design iGuzzini

iGuzzini

Last information update: January 2024



**Accessory code**  
X211: Dimmable electronic power supply unit DALI/Step-Dim/Middle of the night profile IP20 75W - VIN = 220-240VAC 50/60Hz Iout =350mA

**Technical description**  
DALI 75W dimmable electronic power supply, with STEP-DIM, ASTRO-DIM and MIDNIGHT PROFILE (default) functions, Vin=220÷240 Vac, 50÷60Hz, 50÷60Hz Iout=350mA (SELV) IP20 protection rating.

Colour	Weight (Kg)	Dimension (mm) (*)
Indeterminate (00)	0.26	123x79x33
* The dimensions may change according to production requirements to ensure that performance levels and installation methods are observed.		

**Wiring**  
Make the connections on the appropriate terminal blocks

**Notes**  
Overvoltage protection  
DALI-2 ext. -251 -252 -253

Complies with EN60598-1 and pertinent regulations



Technical data			
Frequency [Hz]:	50/60	Minimum dimming %:	10
Current out [mA]:	350	Overvoltage protection:	10kV Common mode & 6kV Differential mode
Inrush current:	62 A / 202 µs	Control:	DALI-2
Maximum number of LED power supply units of this type per miniature circuit breaker:	B10A: 6 power supply units B16A: 10 power supply units C10A: 10 power supply units C16A: 17 power supply units		