

Last information update: April 2024

Product configuration: P800
P800: Platea Pro**Product code**
P800: Platea Pro**Technical description**

Outdoor luminaire with a Wide Flood optic, designed to use LED lamps. Made up of an optical assembly with a base and an aluminium alloy frame. The painting stage consists of a primer and a liquid acrylic paint, cured at 150 °C, with a high level of weather and UV ray resistance. With a 5 mm thick colourless transparent sodium-calcium glass cover. The product can be tilted by +5°-90° around the vertical plane with a 10° step graduated gauge and fitted with mechanical blocks that guarantee stable aiming of the beam of light. Horizontal aiming is performed using the slots in the base, which allow an ±30° adjustment. High visual comfort. Polymer optic lenses offering high yield and even light distribution. Complete with circuit fitted with Neutral White monochrome power LEDs. Extractable control gear connected with quick-coupling connectors. 220-240V ac 50/60Hz DALI electronic ballast. Replaceable control gear. All the screws used are made of A2 stainless steel.

Installation


The luminaire can be installed at ground level or on walls using the standard base.

Colour

White (01) | Black (04) | Grey (15) | Rust Brown (F5)

Weight (Kg)

5.32

**Mounting**

wall arm/wall surface/ground anchored

Wiring

Luminaire ready for pass-through wiring. Product perfect watertightness at the power cable entry point is guaranteed by 2 nickel-plated brass M24x1.5 cable clamps, suitable for cables with a max external 14mm ø (1.5mm² cross section). Push in terminal board.


Notes

Available accessories include: a refractor for elliptical light flow distribution, diffusing glass, visor, directional flaps, protective grille .


Complies with EN60598-1 and pertinent regulations

**Technical data**

Im system:	3072	Life Time LED 1:	100,000h - L80 - B10 (Ta 25°C)
W system:	34.7	Life Time LED 2:	74,000h - L80 - B10 (Ta 40°C)
Im source:	4100	Lamp code:	LED
W source:	31	Number of lamps for optical assembly:	1
Luminous efficiency (lm/W, real value):	88.5	ZVEI Code:	LED
Im in emergency mode:	-	Number of optical assemblies:	1
Total light flux at or above an angle of 90° [Lm]:	0	Intervallo temperatura ambiente:	from -30°C to 50°C.
Light Output Ratio (L.O.R.) [%]:	75	Power factor:	See installation instructions
Beam angle [°]:	46°	Inrush current:	26 A / 180 µs
CRI (minimum):	80	Maximum number of luminaires of this type per miniature circuit breaker:	B10A: 17 luminaires B16A: 28 luminaires C10A: 29 luminaires C16A: 47 luminaires
Colour temperature [K]:	4000	Overvoltage protection:	10kV Common mode & 6kV Differential mode
MacAdam Step:	3	Control:	DALI-2

Polar

Isolux



UGR diagram

Corrected UGR values (at 4100 lm bare lamp luminous flux)											
Reflect.:		viewed crosswise					viewed endwise				
ceil/cav	walls	work pl.	Room dim	X	Y						
2H	2H	18.9	19.5	19.2	19.8	20.0	18.9	19.5	19.2	19.8	20.0
3H		19.0	19.6	19.3	19.9	20.1	18.9	19.5	19.2	19.8	20.1
4H		19.0	19.5	19.3	19.8	20.1	18.9	19.4	19.2	19.7	20.0
6H		18.9	19.4	19.3	19.7	20.1	18.8	19.3	19.2	19.6	20.0
8H		18.9	19.4	19.3	19.7	20.0	18.8	19.3	19.2	19.6	19.9
12H		18.9	19.3	19.2	19.7	20.0	18.8	19.2	19.1	19.6	19.9
4H	2H	18.9	19.4	19.2	19.7	20.0	19.0	19.5	19.3	19.8	20.1
3H		19.1	19.5	19.4	19.9	20.2	19.1	19.5	19.4	19.9	20.2
4H		19.0	19.4	19.4	19.8	20.2	19.0	19.4	19.4	19.8	20.2
6H		19.0	19.3	19.4	19.7	20.2	19.0	19.3	19.4	19.7	20.2
8H		18.9	19.3	19.4	19.7	20.1	19.0	19.3	19.4	19.7	20.1
12H		18.9	19.2	19.3	19.6	20.1	18.9	19.2	19.4	19.6	20.1
8H	4H	19.0	19.3	19.4	19.7	20.1	18.9	19.3	19.4	19.7	20.1
6H		18.9	19.2	19.4	19.6	20.1	18.9	19.2	19.4	19.6	20.1
8H		18.8	19.1	19.3	19.5	20.0	18.8	19.1	19.3	19.5	20.0
12H		18.8	19.0	19.3	19.5	20.0	18.8	19.0	19.3	19.5	20.0
12H	4H	18.9	19.2	19.4	19.6	20.1	18.9	19.2	19.3	19.6	20.1
6H		18.8	19.1	19.3	19.5	20.0	18.8	19.1	19.3	19.5	20.0
8H		18.8	19.0	19.3	19.5	20.0	18.8	19.0	19.3	19.5	20.0
Variations with the observer position at spacing:											
S =	1.0H	2.8 / -2.8				2.8 / -2.8					
	1.5H	5.1 / -4.3				5.1 / -4.3					
	2.0H	6.9 / -5.5				6.9 / -5.5					