

Laser Blade XS



Design iGuzzini

iGuzzini

Last information update: June 2025

Product configuration: RA76

RA76: Frame 9 cells - Wideflood beam - LED



Product code

RA76: Frame 9 cells - Wideflood beam - LED

Technical description

Square miniaturised recessed luminaire with 9 optical elements for LED lamps - fixed optics. Despite the ultracompact size of the product, the patented technology of the optic system guarantees an efficient flow and a high level of visual comfort. Main body with die-cast aluminium radiant surface, version with perimeter surface frame. Metallised, thermoplastic, high definition Opti Beam reflectors, integrated in a set-back position in the anti-glare screen. Supplied with DALI power supply unit connected to the luminaire.

Installation

Recessed with steel wire springs for false ceilings from 1 to 25 mm thick - preparation hole 60 x 60.

Colour

White (01) | Black / Black (43) | Black / White (47) | White/Gold (41)* | Grey / Black (74)* | White / burnished chrome (E7)*

Weight (Kg)

0.3

* Colours on request

Mounting

wall recessed|ceiling recessed

Wiring

On the power supply unit with terminal board included.

Complies with EN60598-1 and pertinent regulations



Technical data

lm system:	1287	Colour temperature [K]:	3500
W system:	17.7	MacAdam Step:	2
lm source:	1550	Life Time LED 1:	> 50,000h - L80 - B10 (Ta 25°C)
W source:	15	Voltage [Vin]:	230
Luminous efficiency (lm/W, real value):	72.7	Lamp code:	LED
lm in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	83	Number of optical assemblies:	1
Beam angle [°]:	58°	Control:	DALI-2
CRI (minimum):	90		


Polar

	CIE nL 0.83 100-100-100-100-83 UGR 16.1-16.1 DIN A.61 UTE 0.83A+0.00T F*1=996 F*1+F*2=1000 F*1+F*2+F*3=1000 CIBSE LG3 L<1500 cd/m² at 65° UGR<19 L<1500 cd/mq @65°			
	h	d	Em	Emax
	2	2.2	326	406
	4	4.4	81	102
	6	6.7	36	45
	8	8.9	20	25

Utilisation factors

R	77	75	73	71	55	53	33	00	DRR
K0.8	75	71	68	66	70	68	68	65	78
1.0	78	75	72	70	74	72	71	69	83
1.5	82	79	77	76	78	77	76	73	89
2.0	85	83	81	80	82	80	79	77	93
2.5	86	85	84	83	84	83	82	79	96
3.0	87	86	85	85	85	84	83	81	98
4.0	88	87	87	86	86	86	84	82	99
5.0	89	88	88	88	87	86	85	83	100

Luminance curve limit



UGR diagram

Corrected UGR values (at 1550 lm bare lamp luminous flux)											
Reflect.: ceiling/cav walls work pl. Room dim x y		viewed crosswise					viewed endwise				
2H	2H	10.0	17.2	10.9	17.5	17.7	10.0	17.2	10.9	17.5	17.7
	3H	10.5	17.0	10.8	17.3	17.6	10.5	17.0	10.8	17.3	17.6
	4H	10.4	10.9	10.8	17.2	17.5	10.4	10.9	10.8	17.2	17.5
	6H	10.4	10.8	10.7	17.1	17.5	10.4	10.8	10.7	17.1	17.5
	8H	10.3	10.8	10.7	17.1	17.4	10.3	10.8	10.7	17.1	17.4
	12H	10.3	10.7	10.7	17.0	17.4	10.3	10.7	10.7	17.0	17.4
4H	2H	10.4	10.9	10.8	17.2	17.5	10.4	10.9	10.8	17.2	17.5
	3H	10.3	10.7	10.7	17.0	17.4	10.3	10.7	10.7	17.0	17.4
	4H	10.2	10.6	10.6	10.9	17.3	10.2	10.6	10.6	10.9	17.3
	6H	10.1	10.4	10.5	10.8	17.2	10.1	10.4	10.5	10.8	17.2
	8H	10.1	10.4	10.5	10.8	17.2	10.1	10.4	10.5	10.8	17.2
	12H	10.0	10.3	10.5	10.7	17.2	10.0	10.3	10.5	10.7	17.2
8H	4H	10.1	10.4	10.5	10.8	17.2	10.1	10.4	10.5	10.8	17.2
	6H	10.0	10.2	10.4	10.7	17.1	10.0	10.2	10.4	10.7	17.1
	8H	15.9	10.1	10.4	10.6	17.1	15.9	10.1	10.4	10.6	17.1
	12H	15.9	10.0	10.4	10.5	17.0	15.9	10.0	10.4	10.5	17.0
12H	4H	10.0	10.3	10.5	10.7	17.2	10.0	10.3	10.5	10.7	17.2
	6H	15.9	10.1	10.4	10.6	17.1	15.9	10.1	10.4	10.6	17.1
	8H	15.9	10.0	10.4	10.5	17.0	15.9	10.0	10.4	10.5	17.0
Variations with the observer position at spacing:											
S =		1.0H					0.5 / -24.9				
		1.5H					9.4 / -25.6				
		2.0H					11.4 / -25.8				