

Project name: _____

Type: _____



A discreet and versatile line of products created to meet the multiple requirements of light in urban architecture and residential areas. A compact and essential design, specifically designed to facilitate installation and maintenance operations and guarantee minimal visual impact.

Luminaire characteristics:

Power input: 5W

Lumens: 185 or 200lm

Luminaire efficacy: 37 or 40lm/W

Source: White LED (LM-80 Tested)

3000K: 80CRI

4000K: 80CRI.

Lumen maintenance: LM-79 tested.

80% of initial lumens at 66 000 hours - L80 (Ta25C)

80% of initial lumens at 66 000 hours - L80 (Ta40C)

Optics: Available in Flood beam.

Mounting: Ceiling mounted, installs on a standard 4" Junction box.

Material:

body: Die-cast aluminum

Reflector: Anodized aluminum

Diffuser: Tempered glass.

Hardware: Stainless steel screws

Electrical: See remote power supply options page 3.


Finish: Gray (RAL9007) or White (RAL9016) painted finish with a high level of weather and UV resistance. The semi-gloss finish coating is electrostatically applied, durable acrylic enamel baked at high temperatures for superior color retentive finish.

Weight: 0.9lbs (0.4kg).


Warranty: 5 year limited warranty.

Certification: cULus listed for wet location.

Ratings: IP66, IK07



SIDE VIEW



BOTTOM VIEW

Project name: _____

Type: _____


PHOTOMETRIC DATA

Visit iguzzini.com/us for complete photometric data.

LOAD (W)	CCT (K)	CRI	OPTIC	LUMENS (lm)	EFFICACY (lm / w)	MAX CANDENA (cd)	MODELS
5W	3000K	80	FLOOD	185	37	490	I.BK07
	4000K			200	40	535	I.BX06

	Center Beam fc	Beam Width
2.0ft	134 fc	1,0 ft
4.0ft	33,5 fc	1,9 ft
6.0ft	14,9 fc	2,9 ft
8.0ft	8,38 fc	3,8 ft
10.0ft	5,36 fc	4,8 ft
12.0ft	3,72 fc	5,8 ft

3000K - 80 CRI - 26° Flood



Project name: _____

Type: _____

ORDERING INFO

<p>MODEL - FINISH</p> <p>MODEL</p> <p><input type="radio"/> I.BK06 - 4000K</p> <p><input type="radio"/> I.BK07 - 3000K</p>	<p>FINISH</p> <p><input type="radio"/> 01 - White</p> <p><input type="radio"/> 15 - Gray</p>	<p>REMOTE POWER SUPPLY OPTION</p> <p>REMOTE POWER SUPPLY (TO BE ORDERED SEPARATELY) Requirements for (1) fixture: 500mA, 5V nominal value</p> <p><input type="radio"/> 4444-0500-006-UNV-ND</p> <p><input type="radio"/> 4548-0500-006-UNV-ND</p>
---	---	--

REMOTE POWER SUPPLY OPTION
(TO BE ORDERED SEPARATELY)

Watts	Min-Max	Voltage	Rated	Dimming protocol	Box dimensions	Max distance 18AWG	Code
6	1*	120-277V	Indoor	None	6" X 4" X 3" (152 X 102 X 76mm)	20ft (6m)	4444-0500-006-UNV-ND
6	1*	120-277V	Outdoor	None	4" X 7" X 3" (102 X 178 X 76mm)	20ft (6m)	4548-0500-006-UNV-ND

* The Total power of all connected luminaires may not be higher than the power of the driver.

WIRING DIAGRAMS

*Multiple luminaires must be connected in series (home run or fixture chain)

