

**Constant current power supply unit not dimm. IP68 17W with 2 outgoing cables L = 400 - I out = 350 mA - Dimensions: 122x54x26 mm**

Design iGuzzini

iGuzzini

Last information update: September 2023

**Accessory code**

X644: Constant current power supply unit not dimm. IP68 17W with 2 outgoing cables L = 400 - I out = 350 mA - Dimensions: 122x54x26 mm



**Technical description**

Constant current non-dimmable electronic ballast I=350 mA 17 W. Input  $V_{in}=220\pm 240$  Vac 50÷60 Hz. SELV output. The product features include a high level of mains spike protection, 4 kV differential mode, 4 kV common mode, short circuit protection, overcurrent and overtemperature protection. Usage temperature: -40°C / +60°C.

**Installation**

Positioned on top of or inside boxes with suitable drainage. Fitted with slots for fastening with screws, if required.

Colour	Weight (Kg)	Dimension (mm) (*)
Indeterminate (00)	0.3	122x54x26

\* The dimensions may change according to production requirements to ensure that performance levels and installation methods are observed.

**Wiring**

Fitted with 2 x 400 mm long primary and secondary outlet cables.

**Notes**

SELV, EL

Complies with EN60598-1 and pertinent regulations



**Technical data**

Frequency [Hz]:	50/60	Maximum number of LED power supply units of this type per miniature circuit breaker:	B10A: 31 power supply units
Current out [mA]:	350		B16A: 50 power supply units
Inrush current:	5 A / 50 $\mu$ s		C10A: 52 power supply units C16A: 85 power supply units
		Overvoltage protection:	4kV Common mode & 4kV Differential mode