

Last information update: April 2024

**Product code**

Q986.Y: adjustable luminaire - Ø 96 mm - warm white - flood optic - frame

**Technical description**

Round adjustable luminaire designed to use an LED lamp with C.O.B. technology in a warm white colour tone 2700K (CRI 90). Version with rim for surface-mounting. Painted, die-cast aluminium body. Lower reflector vacuum-metallised with aluminium vapours with an anti-scratch protective layer. Anodised aluminium upper reflector. Black, zinc-plated sheet steel bracket. The luminaire can be rotated 30° relative to the horizontal plane and 358° about the vertical axis. The luminaire is fitted with mechanical locks for light beam aiming. Painted extruded aluminium dissipater.

**Installation**

Recessed using torsion springs which allow easy installation in false ceilings with thickness ranging from 1 mm to 25 mm.

**Colour**

White / Aluminium (39)


**Mounting**

ceiling recessed

**Wiring**

Product complete with DALI components

Complies with EN60598-1 and pertinent regulations



IP20

IP23

On the visible part of  
the product once installed**Technical data**

lm system:	579 (*)	CRI:	90
W system:	16.3 (*)	Colour temperature [K]:	2700
lm source:	1450 (*)	Number of lamps for optical assembly:	1
W source:	14 (*)	ZVEI Code:	LED
Luminous efficiency (lm/W, real value):	35.52 (*)	Number of optical assemblies:	1
lm in emergency mode:	-	Control:	DALI-2
Beam angle [°]:	35° (*)		