Design Artec Studio

iGuzzini

Last information update: May 2025

Product configuration: QC36

QC36: Palco linear surface 2 x Ø19 - medium - remote driver



Product code


QC36: Palco linear surface 2 x Ø19 - medium - remote driver Attention! Code no longer in production

Technical description

Linear luminaire for surface installation with 2 miniaturised adjustable spotlights. Spotlight bodies with a cast zamak dissipation system and rotation units - extruded aluminium linear surface structure - shaped steel fixing plate - extruded aluminium linear surface structure with mechanical coupling system - thermoplastic side end caps. The spotlight swivel joints allow the spotlight to be rotated by 360° and tilted by 90°. The set back position of the optic units guarantees a high level of visual comfort with thermoplastic high definition lenses. Ballast not included, available with separate code.

Installation

Installation surface plate fastening - structure attached using a mechanical locking mechanism - insertion of side end caps. This specific locking system can be installed next to linear versions so as to create a continuous external line.



Colour

White (01) | Black (04)

Weight (Kg)

0.18

Mounting

wall surface|ceiling surface

Wiring

Output cables for connecting to power supply line.

Complies with EN60598-1 and pertinent regulations



IP20











Technical data Im system: 255 CRI (minimum): 90 Colour temperature [K]: W system: 3000 190 Im source: MacAdam Step: W source: Life Time LED 1: > 50,000h - L80 - B10 (Ta 25°C) Luminous efficiency (lm/W, 63.7 LED Lamp code: real value): Number of lamps for optical 1 Im in emergency mode: assembly: Total light flux at or above ZVEI Code: LED 0 an angle of 90° [Lm]: Number of optical 2 assemblies: Light Output Ratio (L.O.R.) 67 [%]: LED current [mA]: 700 24° Beam angle [°]:

Polar

Imax=660 cd	Lux			
90° 180° 90°	h	d	Em	Emax
	1	0.4	542	660
	2	0.9	135	165
750	3	1.3	60	73
α=24°	4	1.7	34	41