

Last information update: July 2025

**Accessory code**

PF75: DALI IP20 200 W dimmable power supply - Vin = 220-240 Vac - Vout = 48 Vdc - For Libera luminaires only

**Technical description**

200 W DALI dimmable constant voltage electronic power supply - Vout 48 V PWM. Product features include short circuit protection, overcurrent and overtemperature protection.

**Installation**

Consult the luminaire instruction sheet to see how many products you can connect. Fitted with slots for fastening with screws, if required.

Colour	Weight (Kg)	Dimension (mm) (*)
Indeterminate (00)	0.33	325x43x30

\* The dimensions may change according to production requirements to ensure that performance levels and installation methods are observed.

**Wiring**Input and output terminals on opposite sides (cable cross-section up to 1.5 mm<sup>2</sup>). Cable clamp on primary side+DALI and cable clamp on secondary side.**Notes**

A switch-dim control can also be used as an alternative to DALI. Standard: EN 62386-101 / 102 / 207 (including part 251, 252, 253), EN 50172 for use in central battery systems, EN 60598-2-22 suitable for emergency lighting installations.

Complies with EN60598-1 and pertinent regulations

**Technical data**

Frequency [Hz]:	0/50/60	Overvoltage protection:	2kV Common mode & 1kV Differential mode
Inrush current:	89 A / 275 µs	Control:	DALI-2
Maximum number of LED power supply units of this type per miniature circuit breaker:	B10A: 3 power supply units B16A: 6 power supply units C10A: 6 power supply units C16A: 10 power supply units		