


Last information update: April 2024

**Product code**

Q968.Y: Fixed circular recessed luminaire - Ø125 mm - warm white - wide flood optic - UGR<19

Technical description

Fixed round luminaire designed to use a LED lamp with C.O.B. technology. Version with rim for surface-mounting. Reflector vacuum-metallised with aluminium vapours with an anti-scratch protective layer. Die-cast aluminium body and passive dissipation system. Product complete with LED lamp in warm white colour tone CRI 90 (2700K). General light emission, with controlled luminance UGR<19 1500 cd/m² α>65° wide flood optic.

Installation

Recessed using torsion springs which allow easy installation in false ceilings with thickness ranging from 1 mm to 20 mm.

Colour

White / Aluminium (39)

Mounting

ceiling recessed

Wiring

product complete with DALI components

Complies with EN60598-1 and pertinent regulations



IP20

IP54

On the visible part of
the product once installed

pending

Technical data

lm system:	1538 (*)	CRI:	90
W system:	18.9 (*)	Colour temperature [K]:	2700
lm source:	1900 (*)	Number of lamps for optical assembly:	1
W source:	17 (*)	ZVEI Code:	LED
Luminous efficiency (lm/W, real value):	65.5 (*)	Number of optical assemblies:	1
lm in emergency mode:	-	Control:	DALI-2
Beam angle [°]:	64° (*)		