Design iGuzzini

iGuzzini Bespoke

Last information update: February 2025

## **Product configuration: SI28**

SI28: Pole-mounted system – ASF optic – Warm White – Midnight preset / ZHAGA – CRI70



## Product code


SI28: Pole-mounted system – ASF optic – Warm White – Midnight preset / ZHAGA – CRI70

# Technical description

Outdoor luminaire with direct light street optic. Die-cast aluminium alloy optical assembly with steel spring and 4mm thick tempered glass. Option of ± 15° tilt adjustment in relation to the road surface. The IP rating is guaranteed by a silicone gasket. The product is supplied with an output cable L=500mm long. The product can be installed with a pole-top or lateral mounting using an attachment (to be purchased separately as an accessory). The component assembly is opened thanks to a hinge, so it is tool-free. Product fitted with a multi-pole Zhaga 4 Pin socket. All external screws are made of stainless steel.

#### Inctallation

The product can be installed with a pole-top or lateral mounting using an attachment (Ø60mm o Ø76mm) to be purchased separately as an accessory. Two adapters for Ø42mm or Ø46mm poles are also available as accessories.



Colour Grey (RAL 7010) (U9) Weight (Kg) 2.84

# Mounting

pole-top

Complies with EN60598-1 and pertinent regulations

Ш	Ik

K10 IP66





Technical data			
Im system:	6750	Life Time LED 2:	100,000h - L90 - B10 (Ta 40°C)
W system:	43.5	Voltage [Vin]:	230
Im source:	-	Lamp code:	LED
W source:	-	Number of lamps for optical	1
Luminous efficiency (lm/W,	nous efficiency (lm/W, 155.2 assembly:		
real value):		ZVEI Code:	LED
Im in emergency mode:	-	Number of optical	1
Total light flux at or above	0	assemblies:	
an angle of 90° [Lm]:		Intervallo temperatura	from -40°C to 50°C.
Light Output Ratio (L.O.R.)	100	ambiente:	
[%]:		Power factor:	See installation instructions
CRI (minimum):	70	Inrush current:	28.4 A / 270 μs
Colour temperature [K]:	3000	Minimum dimming %:	15
MacAdam Step:	5	Overvoltage protection:	10kV Common mode & 10kV
Life Time LED 1:	100,000h - L90 - B10 (Ta 25°C)		Differential mode

## Polar

