# Laser Blade

Last information update: October 2024

Product code
2567: Minimal section 2 x 5 LEDs - Wall Washer

Technical description
Linear recessed miniaturised luminaire for LED lamps, specialised for vertical wall lighting. The patented optic system guarantees a homogeneous and effective emission on the wall, as well as avoiding shadow zones near the ceiling. Main body with die-cast aluminium radiant surface, minimal (frameless) version for mounting flush with the ceiling. For recessed installation in a false ceiling a specific adapter is required that is available with a separate item code. Flux enhancer - superpure aluminium reflector - asymmetrical textured PMMA screen - black polycarbonate internal perimeter frame. Supplied with a power supply unit connected to the luminaire.

Installation
The recess body is inserted in the specific adapter installed previously by means of a steel wire spring - check the thickness of the false ceiling and use a compatible frame available with a separate item code.

Colour
Black (04)

Mounting
wall recessed|ceiling recessed

Wiring
on power supply box: screw connections.

Complies with EN60598-1 and pertinent regulations

IP20 IP43   On the visible part of the product once installed

pending   pending

Technical data

lm system:	890 (*)	CRI:	90
W system:	21 (*)	Colour temperature [K]:	3500
lm source:	2224 (*)	Number of lamps for optical assembly:	1
W source:	21 (*)		
Luminous efficiency (lm/W, real value):	42.0 (*)	ZVEI Code:	LED
lm in emergency mode:	-	Number of optical assemblies:	1
		Control:	DALI-2

265
56
29
33X270