## Blade R downlight

Design iGuzzini iGuzzini

Last information update: October 2024

Product configuration: QW41

QW41: Round fixed luminaire - Per Blade R Ø 170 mm.



QW41: Round fixed luminaire - Per Blade R Ø 170 mm.

## **Technical description**

Product code

Round fixed luminaire designed to use LED lamps with C.o.B. technology. Version compatible with Blade R diam 170mm (18LED) complete with device for coupling it to the luminaire and DALI control gear with DT8 control System. Reflector vacuum-metallised with aluminium vapours with an anti-scratch protective layer. Dissipater made of painted grey die-cast aluminium. Product complete with Tunable White LED with a colour change temperature from 2700K to 6500K. Light emission UGR<19 L<3000 cd/m2 ideal for environments with video terminals.

## Installation

Downlight accessory for Blade R diam 170mm (18LED)

Colour Weight (Kg)

White / Aluminium (39) | Black / Aluminium (40) 0.55

Complies with EN60598-1 and pertinent regulations



















## Technical data 808.5 Im system: Colour temperature [K]: Tunable white W system: 9.6 Life Time LED 1: > 50,000h - L80 - B10 (Ta 25C) Im source: 1050 Lamp code: W source: Number of lamps for optical 1 6.7 assembly: Luminous efficiency (lm/W, 84.22 real value): ZVEI Code: LED Number of optical Im in emergency mode: Total light flux at or above assemblies: 0.0 an angle of 90° [Lm]: Power factor: See installation instructions Light Output Ratio (L.O.R.) 77 Maximum number of [%]: luminaires of this type per B10A: 13 luminaires 64° miniature circuit breaker: B16A: 22 luminaires Beam angle [°]: C10A: 22 luminaires CRI: 80 C16A: 37 luminaires Overvoltage protection: 0kV Common mode & 0kV Differential mode Control: DALI-2

